

NTLJS3180PZ

Power MOSFET

-20 V, -7.7 A, μ Cool™ Single P-Channel, ESD, 2x2 mm WDFN Package

Features

- WDFN 2x2 mm Package with Exposed Drain Pads for Excellent Thermal Conduction
- Lowest $R_{DS(on)}$ Solution in 2x2 mm Package
- Footprint Same as SC-88 Package
- Low Profile (< 0.8 mm) for Easy Fit in Thin Environments
- ESD Protected
- This is a Pb-Free Device

Applications

- Optimized for Battery and Load Management Applications in Portable Equipment
- High Side Load Switch
- Battery Switch
- DC-DC Converters

MAXIMUM RATINGS ($T_J = 25^\circ\text{C}$ unless otherwise noted)

| Parameter | | Symbol | Value | Unit |
|-------------------------------------------------------------------|--------------------|--------------------------|--------------|------------------|
| Drain-to-Source Voltage | | V_{DSS} | -20 | V |
| Gate-to-Source Voltage | | V_{GS} | ± 8.0 | V |
| Continuous Drain Current (Note 1) | Steady State | $T_A = 25^\circ\text{C}$ | -5.9 | A |
| | | $T_A = 85^\circ\text{C}$ | -4.2 | |
| | $t \leq 5$ s | $T_A = 25^\circ\text{C}$ | -7.7 | |
| Power Dissipation (Note 1) | Steady State | $T_A = 25^\circ\text{C}$ | 1.9 | W |
| | | | $t \leq 5$ s | |
| Continuous Drain Current (Note 2) | Steady State | $T_A = 25^\circ\text{C}$ | -3.5 | A |
| | | $T_A = 85^\circ\text{C}$ | -2.5 | |
| Power Dissipation (Note 2) | Steady State | $T_A = 25^\circ\text{C}$ | 0.7 | W |
| Pulsed Drain Current | $t_p = 10$ μ s | I_{DM} | -23 | A |
| Operating Junction and Storage Temperature | | T_J, T_{STG} | -55 to 150 | $^\circ\text{C}$ |
| Source Current (Body Diode) (Note 2) | | I_S | -2.8 | A |
| Lead Temperature for Soldering Purposes (1/8" from case for 10 s) | | T_L | 260 | $^\circ\text{C}$ |

Stresses exceeding Maximum Ratings may damage the device. Maximum Ratings are stress ratings only. Functional operation above the Recommended Operating Conditions is not implied. Extended exposure to stresses above the Recommended Operating Conditions may affect device reliability.


1. Surface Mounted on FR4 Board using 1 in sq pad size (Cu area = 1.127 in sq [2 oz] including traces).
2. Surface Mounted on FR4 Board using the minimum recommended pad size, (30 mm², 2 oz Cu).




ON Semiconductor®

<http://onsemi.com>


| $V_{(BR)DSS}$ | $R_{DS(on)}$ MAX | I_D MAX |
|---------------|-------------------------|-----------|
| -20 V | 38 m Ω @ -4.5 V | -7.7 A |
| | 50 m Ω @ -2.5 V | |
| | 75 m Ω @ -1.8 V | |
| | 200 m Ω @ -1.5 V | |



P-CHANNEL MOSFET




MARKING DIAGRAM



AA = Specific Device Code
M = Date Code
▪ = Pb-Free Package
(Note: Microdot may be in either location)

PIN CONNECTIONS



(Top View)

ORDERING INFORMATION

| Device | Package | Shipping† |
|----------------|-----------|------------------|
| NTLJS3180PZTAG | WDFN6 | 3000/Tape & Reel |
| NTLJS3180PZTBG | (Pb-Free) | |

†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specification Brochure, BRD8011/D.

NTLJS3180PZ

THERMAL RESISTANCE RATINGS

| Parameter | Symbol | Max | Unit |
|-----------------------------------------------------|-----------------|-----|------|
| Junction-to-Ambient – Steady State (Note 3) | $R_{\theta JA}$ | 65 | °C/W |
| Junction-to-Ambient – Steady State Min Pad (Note 4) | $R_{\theta JA}$ | 180 | |
| Junction-to-Ambient – $t \leq 5$ s (Note 3) | $R_{\theta JA}$ | 38 | |

3. Surface Mounted on FR4 Board using 1 in sq pad size (Cu area = 1.127 in sq [2 oz] including traces).
 4. Surface Mounted on FR4 Board using the minimum recommended pad size (30 mm², 2 oz Cu).

MOSFET ELECTRICAL CHARACTERISTICS ($T_J = 25^\circ\text{C}$ unless otherwise noted)

| Parameter | Symbol | Test Conditions | Min | Typ | Max | Unit |
|-----------|--------|-----------------|-----|-----|-----|------|
|-----------|--------|-----------------|-----|-----|-----|------|

OFF CHARACTERISTICS

| | | | | | | |
|-----------------------------------------------------------|-------------------|-------------------------------------------------|--------------------------|------|----------|---------|
| Drain-to-Source Breakdown Voltage | $V_{(BR)DSS}$ | $V_{GS} = 0$ V, $I_D = -250$ μ A | -20 | | | V |
| Drain-to-Source Breakdown Voltage Temperature Coefficient | $V_{(BR)DSS}/T_J$ | $I_D = -250$ μ A, Ref to 25°C | | -5.0 | | mV/°C |
| Zero Gate Voltage Drain Current | I_{DSS} | $V_{DS} = -16$ V, $V_{GS} = 0$ V | $T_J = 25^\circ\text{C}$ | | -1.0 | μ A |
| | | | $T_J = 85^\circ\text{C}$ | | -10 | |
| Gate-to-Source Leakage Current | I_{GSS} | $V_{DS} = 0$ V, $V_{GS} = \pm 8.0$ V | | | ± 10 | μ A |

ON CHARACTERISTICS (Note 5)

| | | | | | | |
|----------------------------------------|------------------|------------------------------------------|-------|-----|------|------------|
| Gate Threshold Voltage | $V_{GS(TH)}$ | $V_{GS} = V_{DS}$, $I_D = -250$ μ A | -0.45 | | -1.0 | V |
| Gate Threshold Temperature Coefficient | $V_{GS(TH)}/T_J$ | | | 3.0 | | mV/°C |
| Drain-to-Source On-Resistance | $R_{DS(on)}$ | $V_{GS} = -4.5$ V, $I_D = -3.0$ A | | 30 | 38 | m Ω |
| | | $V_{GS} = -2.5$ V, $I_D = -3.0$ A | | 40 | 50 | |
| | | $V_{GS} = -1.8$ V, $I_D = -2.0$ A | | 55 | 75 | |
| | | $V_{GS} = -1.5$ V, $I_D = -1.8$ A | | 85 | 200 | |
| Forward Transconductance | g_{FS} | $V_{DS} = -16$ V, $I_D = -3.0$ A | | 7.7 | | S |

CHARGES, CAPACITANCES AND GATE RESISTANCE

| | | | | | | |
|------------------------------|--------------|--------------------------------------------------------|--|------|------|----|
| Input Capacitance | C_{ISS} | $V_{GS} = 0$ V, $f = 1.0$ MHz, $V_{DS} = -16$ V | | 1100 | | pF |
| Output Capacitance | C_{OSS} | | | 180 | | |
| Reverse Transfer Capacitance | C_{RSS} | | | 130 | | |
| Total Gate Charge | $Q_{G(TOT)}$ | $V_{GS} = -4.5$ V, $V_{DS} = -16$ V, $I_D = -3.0$ A | | 13 | 19.5 | nC |
| Threshold Gate Charge | $Q_{G(TH)}$ | | | 0.5 | | |
| Gate-to-Source Charge | Q_{GS} | | | 1.4 | | |
| Gate-to-Drain Charge | Q_{GD} | | | 4.2 | | |

SWITCHING CHARACTERISTICS (Note 6)

| | | | | | | |
|---------------------|--------------|------------------------------------------------------------------------------|--|-----|--|----|
| Turn-On Delay Time | $t_{d(ON)}$ | $V_{GS} = -4.5$ V, $V_{DD} = -10$ V, $I_D = -3.0$ A, $R_G = 3.0$ Ω | | 8.0 | | ns |
| Rise Time | t_r | | | 15 | | |
| Turn-Off Delay Time | $t_{d(OFF)}$ | | | 70 | | |
| Fall Time | t_f | | | 67 | | |

DRAIN-SOURCE DIODE CHARACTERISTICS

| | | | | | | | |
|--------------------------|----------|------------------------------------------------------------------|---------------------------|--|------|------|----|
| Forward Recovery Voltage | V_{SD} | $V_{GS} = 0$ V, $I_S = -2.0$ A | $T_J = 25^\circ\text{C}$ | | -0.7 | -1.0 | V |
| | | | $T_J = 125^\circ\text{C}$ | | -0.6 | | |
| Reverse Recovery Time | t_{RR} | $V_{GS} = 0$ V, $dI_{SD}/dt = 100$ A/ μ s, $I_S = -2.0$ A | | | 60 | | ns |
| Charge Time | t_a | | | | 16 | | |
| Discharge Time | t_b | | | | 44 | | |
| Reverse Recovery Time | Q_{RR} | | | | 41 | | nC |

5. Pulse Test: Pulse Width ≤ 300 μ s, Duty Cycle $\leq 2\%$.
 6. Switching characteristics are independent of operating junction temperatures.

NTLJS3180PZ

TYPICAL PERFORMANCE CURVES ($T_J = 25^\circ\text{C}$ unless otherwise noted)




Figure 1. On-Region Characteristics




Figure 2. Transfer Characteristics




Figure 3. On-Resistance versus Drain Current




Figure 4. On-Resistance versus Drain Current and Gate Voltage




Figure 5. On-Resistance Variation with Temperature




Figure 6. Drain-to-Source Leakage Current versus Voltage

NTLJS3180PZ

TYPICAL PERFORMANCE CURVES ($T_J = 25^\circ\text{C}$ unless otherwise noted)




Figure 7. Capacitance Variation




Figure 8. Gate-To-Source and Drain-To-Source Voltage versus Total Charge




Figure 9. Resistive Switching Time Variation versus Gate Resistance




Figure 10. Diode Forward Voltage versus Current




Figure 11. Maximum Rated Forward Biased Safe Operating Area

NTLJS3180PZ

TYPICAL PERFORMANCE CURVES ($T_J = 25^\circ\text{C}$ unless otherwise noted)





Figure 12. Thermal Response

NTLJS3180PZ

PACKAGE DIMENSIONS

WDFN6
CASE 506AP-01
ISSUE B




NOTES:

1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 1994.
2. CONTROLLING DIMENSION: MILLIMETERS.
3. DIMENSION b APPLIES TO PLATED TERMINAL AND IS MEASURED BETWEEN 0.15 AND 0.20mm FROM TERMINAL.
4. COPLANARITY APPLIES TO THE EXPOSED PAD AS WELL AS THE TERMINALS.
5. CENTER TERMINAL LEAD IS OPTIONAL. TERMINAL LEAD IS CONNECTED TO TERMINAL LEAD # 4.
6. PINS 1, 2, 5 AND 6 ARE TIED TO THE FLAG.

| DIM | MILLIMETERS | |
|-----|-------------|------|
| | MIN | MAX |
| A | 0.70 | 0.80 |
| A1 | 0.00 | 0.05 |
| A3 | 0.20 REF | |
| b | 0.25 | 0.35 |
| b1 | 0.51 | 0.61 |
| D | 2.00 BSC | |
| D2 | 1.00 | 1.20 |
| E | 2.00 BSC | |
| E2 | 1.10 | 1.30 |
| e | 0.65 BSC | |
| K | 0.15 REF | |
| L | 0.20 | 0.30 |
| L2 | 0.20 | 0.30 |
| J | 0.27 REF | |
| J1 | 0.65 REF | |

SOLDERMASK DEFINED MOUNTING FOOTPRINT



μ Cool is a trademark of Semiconductor Components Industries, LLC (SCILLC).

ON Semiconductor and are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

PUBLICATION ORDERING INFORMATION

LITERATURE FULFILLMENT:
Literature Distribution Center for ON Semiconductor
P.O. Box 5163, Denver, Colorado 80217 USA
Phone: 303-675-2175 or 800-344-3860 Toll Free USA/Canada
Fax: 303-675-2176 or 800-344-3867 Toll Free USA/Canada
Email: orderlit@onsemi.com

N. American Technical Support: 800-282-9855 Toll Free
USA/Canada
Europe, Middle East and Africa Technical Support:
Phone: 421 33 790 2910
Japan Customer Focus Center
Phone: 81-3-5773-3850

ON Semiconductor Website: www.onsemi.com

Order Literature: <http://www.onsemi.com/orderlit>

For additional information, please contact your local Sales Representative

NTLJS3180PZ/D