EV DATE	BY	СНК	DESCRIPTION	ECN	-R	SUP	SCALE N/A DRAWING NO / CAD FILE LCC4_0-12-CUST
1 7/12	JHNU	JHNU	REMOVED NAVY NUMBER	N10883DF-LCC4/0-12-CUS	RGB	RGB	LCC4/0-12-X Copper Lug - Two-Hole, Long Barrel
							CORP. TINLEY PARK, ILLINO
	C	ERTIFIED	D LISTED Wire Connector	.14±.01			
		(H)		<u>+</u> — —	 		
Alternate Industry Die Index No. ( ) on Barrel			(15)		1		.57±.01 .71±.0
Panduit Die Index No. on Barrel			P54				1.56±.04 — Beveled wir entry
Panduit Color Code on Barrel		ode	PURPLE				
C.S.A Certified Wire Connector			Yes				
UL Temp Rating	erature		90° C				── 5.13±.06 ── <b>►</b>
UL Listed Wire Connector			Yes, for applications up to 35kv. Consult cable manufacturer for voltage stress relief instructions with applications greater than 2000 volts.	.63±.04	— 1.75	±.02 -	.53±.02 DIA (2) PLS
Stud Size			1/2 in.	The state of the s	4/0	ICC	PURPLE P
Wire Strip Length		า	1-5/8 in.	1.06±.04	STR CU	LCC4/0-12	PANDUIT  PANDUIT  OURPLE DIE PS4 (15)
Wire Type			Stranded Copper; Class B: Compact, Compressed or Concentric, Class C: Concentric				Color coded barrel markings
Wire Size			4/0 AWG	]			63 R Ref
Plating			Electro-Tin				
Material			High Conductivity Seamless Copper Tube				

THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.