

EVB-USB2250 User Manual Revision B



Copyright © 2009 SMSC or its subsidiaries. All rights reserved.

Circuit diagrams and other information relating to SMSC products are included as a means of illustrating typical applications. Consequently, complete information sufficient for construction purposes is not necessarily given. Although the information has been checked and is believed to be accurate, no responsibility is assumed for inaccuracies. SMSC reserves the right to make changes to specifications and product descriptions at any time without notice. Contact your local SMSC sales office to obtain the latest specifications before placing your product order. The provision of this information does not convey to the purchaser of the described semiconductor devices any licenses under any patent rights or other intellectual property rights of SMSC or others. All sales are expressly conditional on your agreement to the terms and conditions of the most recently dated version of SMSC's standard Terms of Sale Agreement dated before the date of your order (the "Terms of Sale Agreement"). The product may contain design defects or errors known as anomalies which may cause the product's functions to deviate from published specifications. Anomaly sheets are available upon request. SMSC products are not designed, intended, authorized or warranted for use in any life support or other application where product failure could cause or contribute to personal injury or severe property damage. Any and all such uses without prior written approval of an Officer of SMSC and further testing and/or modification will be fully at the risk of the customer. Copies of this document or other SMSC literature, as well as the Terms of Sale Agreement, may be obtained by visiting SMSC's website at <http://www.smsc.com>. SMSC is a registered trademark of Standard Microsystems Corporation ("SMSC"). Product names and company names are the trademarks of their respective holders.

SMSC DISCLAIMS AND EXCLUDES ANY AND ALL WARRANTIES, INCLUDING WITHOUT LIMITATION ANY AND ALL IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, TITLE, AND AGAINST INFRINGEMENT AND THE LIKE, AND ANY AND ALL WARRANTIES ARISING FROM ANY COURSE OF DEALING OR USAGE OF TRADE. IN NO EVENT SHALL SMSC BE LIABLE FOR ANY DIRECT, INCIDENTAL, INDIRECT, SPECIAL, PUNITIVE, OR CONSEQUENTIAL DAMAGES; OR FOR LOST DATA, PROFITS, SAVINGS OR REVENUES OF ANY KIND; REGARDLESS OF THE FORM OF ACTION, WHETHER BASED ON CONTRACT; TORT; NEGLIGENCE OF SMSC OR OTHERS; STRICT LIABILITY; BREACH OF WARRANTY; OR OTHERWISE; WHETHER OR NOT ANY REMEDY OF BUYER IS HELD TO HAVE FAILED OF ITS ESSENTIAL PURPOSE, AND WHETHER OR NOT SMSC HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

1 Overview

The SMSC EVB-USB2250 is an Ultra Fast USB 2.0 Multi-Slot Flash Media Controller with CF, SD, MS, and xD connectors. The EVB-USB2250 Evaluation Board demonstrates a standalone Hi-Speed Mass Storage Class Peripheral Controller intended for reading and writing to more than 24 popular flash media formats from the Compact Flash[™] (CF), SmartMedia[™] (SM), xD Picture Card[™] (xD), Memory Stick[®] (MS), Secure Digital (SD), and MultiMediaCard[™] (MMC) families.

1.1 Features

- Operates either USB bus-powered or from a single voltage (+5.0 Volts, regulated) 'wall wart' external power supply.
- Supports these media types:
 - Compact Flash[™] 4.1
 - MultiMediaCard[™] 2.0 / 4.2
 - xD Picture Card[™]
 - Smart Media[™] 1.2 / 1.3
 - Secure Digital (SD2.0, HS-SD, HC-SD)
 - Memory Stick[®] 1.43
 - Hi-Speed Memory Stick[™]
 - Memory Stick Pro-HG[™]
 - Memory Stick Duo Memory Stick Pro[™]
- Simultaneous access for up to four memory devices
- Flash memory socket for external firmware
- Single onboard +3.3 Volt regulator
- Internal individual FET power switch for each media socket
- Single 24 MHz crystal clock source
- Media activity LED
- RoHS compliant
- Optional serial EEPROM for customized configuration
- Optional ESD and EMI footprints are provided

1.2 General Description

The EVB-USB2250 is a platform featuring the USB2250 Flash Media Controller. The EVB-USB2250 connects to a USB 2.0 port (J1), and optionally to a 5.0 Volt external supply (JP2: 2.1mm, tip -- POS). The platform provides four media sockets supporting 24 different media formats. This platform demonstrates a small footprint, low-cost implementation of the USB2250 with a rich feature set. The platform features a socket for an onboard EEPROM for configuration and serial number data. The platform also features a socket for a flash memory for external firmware. The schematic for the EVB-USB2250 indicates the components that are required for each programming and configuration option.

2 Hardware Configuration

2.1 Hardware Description

The EVB-USB2250 has one onboard regulator which generates 3.3 Volts from the 5 Volt power supply. The USB2250 generates its own on-chip 1.8 Volt supply. The USB2250 Flash Media Controller consumes power from the 3.3 Volt supply and supplies voltage to all four media connectors. The EVB-USB2250 also supports an optional flash memory for external firmware or an optional serial EEPROM for customized configuration.

2.1.1 External Serial EEPROM

The EVB-USB2250 has a socket (U4) for an optional I²C EEPROM. This option provides custom configuration of the USB2250. USBDM. Please visit <http://www.smSC.com/main/catalog/usb225x.html> to locate the USBDM available in the software release package. Scroll down to the bottom of the page and select "OBJ Hub Card Reader". Then, read and accept the SMSC Software Download Agreement. If you select "Confirm", then you will be taken to the USB225x release package zip file where you can download the tool set. The EVB-USB2250 is compatible with I²C EEPROMs, 256 bytes or larger from several manufacturers in 8-pin DIP packages.

2.1.2 External Flash Memory

The EVB-USB2250 has a socket (U3) for optional flash memory. The flash memory stores external firmware that the USB2250 executes and can be updated in the field. The firmware can be uploaded from the USBDM utility. Most 8-bit wide flash memory that is 128 kilobytes or larger in a 32-pin PLCC package with access time of 70 ns or less are compatible with the EVB-USB2250.

2.1.3 Connector Description

The EVB-USB2250 has a standard set of media storage style connectors, which supports up to 24 popular flash media formats from the CompactFlash[™] (CF), SmartMedia[™] (SM), xD Picture Card[™] (xD), Memory Stick[®] (MS), Secure Digital (SD), and MultimediaCard[™] (MMC) families.

2.1.4 Power Supply

The EVB-USB2250 receives power from either the host via the upstream connector J1 or from J8 depending upon JP1 shunt installation. For host power shunt pins 2 and 3, or for self-powered operation shunt pins 1 and 2 of JP1.

Table 2.1 Connector Descriptions


CONNECTOR	TYPE
J2	SD/MMC4.0
J6	XD
J7	MS Normal Mount
J9	Compact Flash

2.1.5 Layout Considerations

The EVB-USB2250 is designed on four PCB layers--two signal layers and two supply layers. The PCB layer stack is shown in Table 1. All signals are routed on the top and bottom layers. Internal layers are ground and power.

Table 2.2 PCB Layer Stack

Component Side	
Solder mask	
Layer 1 Top	1.3 - 2.3 oz. Cu. finished weight
Pre-preg	4.0 - 4.5 mil FR-4
Layer 2, Ground	1.0 oz., nominal
Core	25 mil FR-4
Layer 3, Power	1.0 oz., nominal
Pre-preg	4.0 - 4.5 mil FR-4
Layer 4, Bottom	1.3 - 2.3 oz. Cu. finished weight
Solder mask	
Solder Side	


Figure 2.1 EVB-USB2250 top view




Figure 2.2 EVB-USB2250 bottom view