

Connector - C-SCFFI 1,5/6,3X0,8 - 3240538

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



Slip-on sleeve, fully isolated, red, 0.5 - 1.5 mm², for plug 6.3 x 0.8 mm

Product Features

- Hard-soldered crimping zone for maximum conductor pull-out forces in connection with CRIMPFOX RCI... pliers
- Easy and reliable conductor entry thanks to 'EASY ENTRY'
- Halogen-free
- Electrolytically tin-plated



Key commercial data

| | |
|------------------------|----------|
| Packing unit | 1 1 |
| Minimum order quantity | 50 1 |
| Custom tariff number | 85366990 |
| Country of origin | China |

Technical data

Dimensions

| | |
|--|---------|
| Length (b) | 21.5 mm |
| Width (a) | 6.3 mm |
| Length of insulation sleeve (c) | 10.5 mm |
| Inner dimension of the insulating collar (d) | 4.3 mm |
| Material thickness (g) | 0.4 mm |

Ambient conditions

| | |
|---------------------------------|-------------------|
| Ambient temperature (operation) | -20 °C ... 105 °C |
| Short-term temperature | 120 °C |
| Max. permanent temperature | 105 °C |

General

Connector - C-SCFFI 1,5/6,3X0,8 - 3240538

Technical data

General

| | |
|------------------|--------------|
| Color | red |
| Stripping length | 7 mm |
| Components | Halogen-free |
| Material | Brass |

Classifications

eCl@ss

| | |
|------------|----------|
| eCl@ss 4.0 | 27140815 |
| eCl@ss 4.1 | 27140815 |
| eCl@ss 5.0 | 27260701 |
| eCl@ss 5.1 | 27260701 |
| eCl@ss 6.0 | 27400209 |
| eCl@ss 7.0 | 27440304 |
| eCl@ss 8.0 | 27440304 |

ETIM

| | |
|----------|----------|
| ETIM 2.0 | EC000516 |
| ETIM 3.0 | EC000516 |
| ETIM 4.0 | EC000516 |
| ETIM 5.0 | EC000516 |

UNSPSC

| | |
|---------------|----------|
| UNSPSC 6.01 | 30211923 |
| UNSPSC 7.0901 | 39121522 |
| UNSPSC 11 | 39121522 |
| UNSPSC 12.01 | 39121522 |
| UNSPSC 13.2 | 39121522 |

Drawings

Connector - C-SCFFI 1,5/6,3X0,8 - 3240538

Dimensioned drawing

