

250-63122

Article Number: 250-63122

Description: Reducer 1.25" to .75" (TSRP2 to TSRP1), PVC, White, 1/bag



| | | |
|-----------------------------|-----------------------------|---|
| Base Data | Local Order Number | TSRP3W-12 |
| | Type | TSRP3-12 |
| | Color | White (WH) |
| | Features and Benefits | <ul style="list-style-type: none"> • Self-locking covers, provide taper resistant security, while the hidden positive latch permits quick re-entry access to power cables. • An integrated flexible hinge allows the raceway to endure numerous openings without stress cracking or discoloration. • Raceways and fittings are UL Listed for power up to 600 Volts and meet UL5A and CSA 22.2 Number 62-93 Standards, to insure compliance with local building codes. Raceway fittings incorporate a minimum 1" bend radius to meet TIA/EIA 568-B and 569-A standards. |
| | Quantity Per | EA |
| | Product Description | HellermannTyton provides a complete line of raceway and fittings to manage connectivity requirements from the telecommunications room to the work area. Each size of raceway offers numerous fittings, offered in electrical ivory, white or office white, including TIA/EIA-568-B compliant 1" bend radius accessories which help ensure consistent data transmission performance of Category 6A, 6 and 5e communications systems. |
| | Short Description | Reducer 1.25" to .75" (TSRP2 to TSRP1), PVC, White, 1/bag |
| | | |
| Material and Specifications | Material | Polyvinylchloride (PVC) |
| | Material Shortcut | PVC |
| | ROHS Compliant | Yes |
| | | |
| Logistic and Packaging | Package Quantity (Imperial) | 1 |
| | Package Quantity (Metric) | 1 |
| | Customs Number(Schedule B) | 3925900000 |
| | | |

250-63122

HellermannTyton
