

# Electronic housing - ME MAX 12,5 3-3 TBUS KMGY - 2279020

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://download.phoenixcontact.com)



Electronic housing, design width 12.5 mm, 3 connection levels per side, for DIN rail bus connectors

#### **Product Features**

- ☑ DIN rail bus connector as an option
- ☑ Plug-in connection with screw, spring-cage or fast connection technology
- ☑ Large front surface for high-pos. plugs or operating and setting elements

- Transparent front cover can be swiveled

### Key commercial data

Packing unit	11
Minimum order quantity	10 1
Weight per Piece (excluding packing)	39.4 GRM
Custom tariff number	85472000
Country of origin	Germany

#### Technical data

#### General

Housing type	Complete housing	
Housing material	Polyamide	
Color	light gray	

#### **Dimensions**

Length	99 mm
Constructional height	114.5 mm



# Electronic housing - ME MAX 12,5 3-3 TBUS KMGY - 2279020

# Technical data

#### **Dimensions**

Width	12.5 mm
Technical data	
Inflammability class according to UL 94	V0
Power dissipation at 20°C in the horizontal mounting position	4.4 W 8.4 W

## Classifications

## eCl@ss

eCl@ss 4.0	27180401
eCl@ss 4.1	27180401
eCl@ss 5.0	27180506
eCl@ss 5.1	27180506
eCl@ss 6.0	27180802
eCl@ss 7.0	27182702
eCl@ss 8.0	27182702

#### **ETIM**

ETIM 2.0	EC001031
ETIM 3.0	EC001031
ETIM 4.0	EC001031
ETIM 5.0	EC001031

### UNSPSC

UNSPSC 6.01	31261501
UNSPSC 7.0901	31261501
UNSPSC 11	31261501
UNSPSC 12.01	31261501
UNSPSC 13.2	31261501

# Approvals

## Approvals

Approvals

**UL** Recognized

Approvals



# Electronic housing - ME MAX 12,5 3-3 TBUS KMGY - 2279020

Ex Approvals		
Approvals submitted		
Approval details		
UL Recognized <b>\$\)</b>		

© Phoenix Contact 2013 - all rights reserved http://www.phoenixcontact.com