




USB A plug 90° SMT mount











DIMENSIONS ARE IN MILLIMETERS

1.0 to 10.0: ± 0.2 mm Over 10.0: ± 0.3 mm

DESCRIPTION:

NOTES

TOLERANCES: Connector, USB A plug, SMT mount, 180°, nickel Up to 1.0: ± 0.1 mm shell, board lock, black insulator

TENSILITY

20802 Sockeye Place #130 Bend, OR 97701 USA tel 541.323.3228 fax 541.323.4202 800 877.670.7118 www.tensility.com

SIZE **PART NUMBER**

54-00011

SCALE: 1:1 SHEET 1 OF 2

5 3 2

RoHS and REACH compliant

Materials

- 1. Shell, steel, nickel plated
- 2. Pins, brass, 5 μ " gold and tin plating
- 3. Insulator, PBT, black

Electrical

Rated voltage: 30 Vdc Rated current: 3 A

Dielectric strength: 1 min @ 500 Vac Insulation resistance: 500 M Ω @ 500 Vdc Contact resistance: 50 mΩ or less

Mechanical

Insertion force: 3.5 kgf maximum Withdrawal force: 1.0 kgf minimum

Durability: 1500 cycle minimum life; less than 100 m Ω contact resistance. minimum 100 MΩ insulation

resistance

Terminal strength: 0.3 kgf in any direction without damage or looseness

Soldering

Solderability: 75% minimum coverage when terminals dipped 2 mm in 245 ±5 °C solder bath for 3 ±0.5 seconds

Solder bath durability: no deformation when immersed in 255 ±5 °C up to surface of the board for 5 seconds or less

Solder iron durability: no deformation when exposed to 350 ±10 °C for 3 ±0.5 seconds

Environmental


Cold test: -25 ±3 °C for 48 hours without deformation Heat test: 70 ±2 °C for 48 hours without deformation Humidity test: 40 ±2 °C and humidity between 90 and 98 % for 48 hours without deformation


5


Operating range

-10 ~ 60°C

USB A plug 90° SMT mount







REVISION A	DATE 9/28/2015	DESCRIPTION Initial release	PREPARED:	NOTES RoHS and REACH compliant	T	TENSILITY			
			TOI FRANCES:			20802 Sockeye Place #130 Bend, OR 97701 USA tel 541.323.3228 fax 541.323.4202 800 877.670.7118 www.tensility.com			
				DESCRIPTION: Connector, USB A plug, SMT mount, 180°, nickel shell, board lock, black insulator	SIZE A	PART NUMBER 54-00011			
						E: 1:1		SHEET 2 OF 2	