



FEATURES:

- ✓ Locking test clips provide the user with an easy means to connect instrumentation to the fine pitch QFP chip leads.
- ✓ The special locking fingers at each corner attach to the body of the chip and hold the clip firmly against the chip leads.
- ✓ Centrally activated locking mechanism allows testing vertical boards.
- ✓ Interfaces with high density EIAJ PQFP (sometimes also described as **TQFP** or **VQFP**) surface mount chip leads.
- ✓ Two-stage alignment assures positive connections.
- ✓ Gold plated connector pins and contacts assure noise free connections.
- ✓ Gold plated .025" square pins provide easy connection with either ribbon cable or discrete jumpers.



Pomona Model	Lead Pitch	Leads "D"	Body "D1"	Chip Height "A"	Critical Dimension "C"*
5770 L	.50mm	30.6 mm	28 mm	3.4 mm	29.6 mm



*** To calculate the "Critical Dimension" refer to manufacture data sheet or measure with calipers to determine the nominal value of "D", "L" and "T".**

$$C = D - 2(L - T)$$

All dimensions are in inches. Tolerances (except noted): .xx = ±.02" (.51 mm), .xxx = ±.005" (.127 mm).
 All specifications are to the latest revisions. Specifications are subject to change without notice.
 Registered trademarks are the property of their respective companies.

Sales: 800-490-2361 Fax: 888-403-3360 Technical Support: 800-241-2060 (technicalsupport@pomonatest.com)
 For "Where to Buy" information, visit the Pomona web site at www.pomonaelectronics.com