


## 1.0-Amp Output Current SiC/GaN MOSFET and IGBT Gate Drive Optocoupler in Stretched SO6

### Data Sheet

#### Description

The ACPL-P347/W347 contains an AlGaAs LED, which is optically coupled to an integrated circuit with a power output stage. This optocoupler is ideally suited for driving SiC/GaN (Silicon Carbide/Gallium Nitride) MOSFETs and IGBTs used in power conversion applications. The high operating voltage range of the output stage provides the drive voltages required by gate-controlled devices. The voltage and high peak output current supplied by this optocoupler make it ideally suited for direct driving SiC/GaN MOSFET and IGBT with ratings up to 1200V/50A.

#### Functional Diagram



Note: A 1  $\mu$ F bypass capacitor must be connected between pins  $V_{CC}$  and  $V_{EE}$ .

#### Truth Table

| LED | $V_{CC} - V_{EE}$<br>POSITIVE GOING<br>(TURN-ON) | $V_{CC} - V_{EE}$<br>NEGATIVE GOING<br>(TURN-OFF) | $V_O$      |
|-----|--|---|------------|
| OFF | 0V to 30V  | 30 to 0V  | LOW        |
| ON  | 0V to 12.1V                                      | 11.1V to 0V                                       | LOW        |
| ON  | 12.1V to 13.9V                                   | 12.9V to 11.1V                                    | TRANSITION |
| ON  | 13.9V to 30V                                     | 30V to 12.9V                                      | HIGH       |

#### Features

- 1.0A maximum peak output current
- Wide operating  $V_{CC}$  range: 15V to 30V
- 110 ns maximum propagation delay
- 50 ns maximum propagation delay difference
- Rail-to-rail output voltage
- 50 kV/ $\mu$ s minimum Common Mode Rejection (CMR) at  $V_{CM} = 1500V$
- LED current input with hysteresis
- ICC = 4.2 mA maximum supply current
- Under Voltage Lock-Out protection (UVLO) with hysteresis
- Industrial temperature range:  $-40^{\circ}C$  to  $+105^{\circ}C$
- Safety Approval
  - UL Recognized 3750V/5000V<sub>RMS</sub> for 1 min.
  - CSA
  - IEC/EN/DIN EN 60747-5-5  $V_{IORM} = 891V/1140V_{peak}$

#### Applications

- SiC/GaN MOSFET and IGBT gate drive
- Motor drives
- Industrial Inverters
- Renewable energy inverters
- Switching power supplies

**CAUTION:** It is advised that normal static precautions be taken in handling and assembly of this component to prevent damage and/or degradation which may be induced by ESD. The components featured in this data sheet are not to be used in military or aerospace applications or environments.

## Ordering Information

ACPL-P347 is UL Recognized with 3750V<sub>RMS</sub> for 1 minute per UL1577. ACPL-W347 is UL Recognized with 5000V<sub>RMS</sub> for 1 minute per UL1577.

| Part Number | Option         | Package        | Surface Mount | Tape and Reel | IEC/EN/DIN EN 60747-5-5 | Quantity      |
|-------------|----------------|----------------|---------------|---------------|-------------------------|---------------|
|             | RoHS Compliant |                |               |               |                         |               |
| ACPL-P347   | -000E          | Stretched SO-6 | X             |               |                         | 100 per tube  |
| ACPL-W347   | -500E          |                | X             | X             |                         | 1000 per reel |
|             | -060E          |                | X             |               | X                       | 100 per tube  |
|             | -560E          |                | X             | X             | X                       | 1000 per reel |

To order, choose a part number from the part number column and combine with the desired option from the option column to form an order entry.

Example 1:

ACPL-P347-560E to order product of Stretched SO-6 Surface Mount package in Tape and Reel packaging with IEC/EN/DIN EN 60747-5-5 Safety Approval in RoHS compliant.


Example 2:

ACPL-W347-000E to order product of Stretched SO-6 Surface Mount package in Tube packaging and RoHS compliant.


Option data sheets are available. Contact your Broadcom sales representative or authorized distributor for information.

# Package Outline Drawing

## ACPL-P347 Stretched SO-6 Package (7 mm Clearance)



## ACPL-W347 Stretched SO-6 Package (8 mm Clearance)



## Recommended Pb-Free IR Profile

Recommended reflow condition as per JEDEC Standard, J-STD-020 (latest revision). Non-Halide Flux should be used.

## Regulatory Information

The ACPL-P347/W347 is approved by the following organizations:

|  |  |
|--|--|
| <b>UL</b>  | Recognized under UL 1577, component recognition program up to $V_{ISO} = 3750V_{RMS}$ (ACPL-P347) and $V_{ISO} = 5000V_{RMS}$ (ACPL-W347). |
| <b>CSA</b>                                       | CSA Component Acceptance Notice #5, File CA 88324  |
| <b>IEC/EN/DIN EN 60747-5-5 (Option 060 Only)</b> | Maximum Working Insulation Voltage $V_{IORM} = 891V_{peak}$ (ACPL-P347) and $V_{IORM} = 1140V_{peak}$ (ACPL-W347)                          |

## IEC/EN/DIN EN 60747-5-5 Insulation Characteristics\* (Option 060)

| Description   | Symbol          | ACPL-P347 Option 060                   | ACPL-W347 Option 060                            | Unit        |
|---|-----------------|--|---|-------------|
| Installation classification per DIN VDE 0110/39, Table 1<br>for rated mains voltage $\leq 150 V_{RMS}$<br>for rated mains voltage $\leq 300 V_{RMS}$<br>for rated mains voltage $\leq 450 V_{RMS}$<br>for rated mains voltage $\leq 600 V_{RMS}$<br>for rated mains voltage $\leq 1000 V_{RMS}$ |                 | I – IV<br>I – IV<br>I – III<br>I – III | I – IV<br>I – IV<br>I – IV<br>I – IV<br>I – III |             |
| Climatic Classification   |                 | 40/105/21                              | 40/105/21                                       |             |
| Pollution Degree (DIN VDE 0110/39)  |                 | 2                                      | 2   |             |
| Maximum Working Insulation Voltage  | $V_{IORM}$      | 891                                    | 1,140   | $V_{peak}$  |
| Input to Output Test Voltage, Method b*<br>$V_{IORM} \times 1.875 = V_{PR}$ , 100% Production Test with $t_m = 1$ sec, Partial discharge $< 5$ pC   | $V_{PR}$        | 1,671                                  | 2,137   | $V_{peak}$  |
| Input to Output Test Voltage, Method a*<br>$V_{IORM} \times 1.6 = V_{PR}$ , Type and Sample Test, $t_m = 10$ sec, Partial discharge $< 5$ pC  | $V_{PR}$        | 1,426                                  | 1,824   | $V_{peak}$  |
| Highest Allowable Overvoltage*<br>(Transient Overvoltage $t_{ini} = 60$ sec)  | $V_{IOTM}$      | 6,000                                  | 8,000   | $V_{peak}$  |
| Safety-limiting values – maximum values allowed in the event of a failure   |                 |  |   |             |
| Case Temperature  | $T_S$           | 175                                    | 175   | $^{\circ}C$ |
| Input Current   | $I_{S, INPUT}$  | 230                                    | 230   | mA          |
| Output Power  | $P_{S, OUTPUT}$ | 600                                    | 600   | mW          |
| Insulation Resistance at $T_S$ , $V_{IO} = 500V$  | $R_S$           | $>10^9$                                | $>10^9$   | $\Omega$    |

\*Refer to IEC/EN/DIN EN 60747-5-5 Optoisolator Safety Standard section of the Broadcom Regulatory Guide to Isolation Circuits, AV02-2041EN for a detailed description of Method a and Method b partial discharge test profiles.

Note: These optocouplers are suitable for “safe electrical isolation” only within the safety limit data. Maintenance of the safety data shall be ensured by means of protective circuits. Surface mount classification is Class A in accordance with CECC 00802.

## Insulation and Safety Related Specifications

| Parameter   | Symbol | ACPL-P347 | ACPL-W347 | Unit | Conditions   |
|---|--------|-----------|-----------|------|--|
| Minimum External Air Gap (Clearance)              | L(101) | 7.0       | 8.0       | mm   | Measured from input terminals to output terminals, shortest distance through air.  |
| Minimum External Tracking (Creepage)              | L(102) | 8.0       | 8.0       | mm   | Measured from input terminals to output terminals, shortest distance path along body.  |
| Minimum Internal Plastic Gap (Internal Clearance) |        | 0.08      | 0.08      | mm   | Through insulation distance conductor to conductor, usually the straight line distance thickness between the emitter and detector. |
| Tracking Resistance (Comparative Tracking Index)  | CTI    | >175      | >175      | V    | DIN IEC 112/VDE 0303 Part 1  |
| Isolation Group                                   |        | IIIa      | IIIa      |      | Material Group (DIN VDE 0110, 1/89, Table 1)   |

### Note:

- All Broadcom data sheets report the creepage and clearance inherent to the optocoupler component itself. These dimensions are needed as a starting point for the equipment designer when determining the circuit insulation requirements. However, once mounted on a printed circuit board, minimum creepage and clearance requirements must be met as specified for individual equipment standards. For creepage, the shortest distance path along the surface of a printed circuit board between the solder fillets of the input and output leads must be considered (the recommended Land Pattern does not necessarily meet the minimum creepage of the device). There are recommended techniques such as grooves and ribs which may be used on a printed circuit board to achieve desired creepage and clearances. Creepage and clearance distances will also change depending on factors such as pollution degree and insulation level.

## Absolute Maximum Ratings

| Parameter  | Symbol              | Min. | Max.     | Unit | Note |
|--|---------------------|------|----------|------|------|
| Storage Temperature  | $T_S$               | -55  | +125     | °C   |      |
| Operating Temperature  | $T_A$               | -40  | +105     | °C   |      |
| Output IC Junction Temperature                                 | $T_J$               |      | 125      | °C   |      |
| Average Input Current  | $I_{F(AVG)}$        |      | 25       | mA   | 1    |
| Peak Transient Input Current (<1 $\mu$ s pulse width, 300 pps) | $I_{F(TRAN)}$       |      | 1        | A    |      |
| Reverse Input Voltage  | $V_R$               |      | 5        | V    |      |
| “High” Peak Output Current                                     | $I_{OH(PEAK)}$      |      | 1.0      | A    | 2    |
| “Low” Peak Output Current                                      | $I_{OL(PEAK)}$      |      | 1.0      | A    | 2    |
| Total Output Supply Voltage                                    | $(V_{CC} - V_{EE})$ | 0    | 35       | V    |      |
| Output Voltage   | $V_{O(PEAK)}$       | -0.5 | $V_{CC}$ | V    |      |
| eOutput IC Power Dissipation                                   | $P_O$               |      | 500      | mW   | 3    |
| Total Power Dissipation  | $P_T$               |      | 550      | mW   | 4    |

## Recommended Operating Conditions

| Parameter             | Symbol              | Min. | Max. | Unit | Note |
|-----------------------|---------------------|------|------|------|------|
| Operating Temperature | $T_A$               | -40  | +105 | °C   |      |
| Output Supply Voltage | $(V_{CC} - V_{EE})$ | 15   | 30   | V    |      |
| Input Current (ON)    | $I_{F(ON)}$         | 7    | 11   | mA   |      |
| Input Voltage (OFF)   | $V_{F(OFF)}$        | -3.6 | +0.8 | V    |      |

## Electrical Specifications (DC)

All typical values are at  $T_A = 25^\circ\text{C}$ ,  $V_{CC} - V_{EE} = 15\text{V}$ ,  $V_{EE} = \text{Ground}$ . All minimum and maximum specifications are at recommended operating conditions ( $T_A = -40^\circ\text{C}$  to  $+105^\circ\text{C}$ ,  $I_{F(\text{ON})} = 7\text{ mA}$  to  $+11\text{ mA}$ ,  $V_{F(\text{OFF})} = -3.6\text{V}$  to  $+0.8\text{V}$ ,  $V_{EE} = \text{Ground}$ ,  $V_{CC} = 15\text{V}$  to  $30\text{V}$ ), unless otherwise noted.

| Parameter   | Symbol                    | Min.           | Typ.           | Max. | Unit  | Test Conditions                                 | Fig. | Note |
|---|---------------------------|----------------|----------------|------|-------|---|------|------|
| High Level Peak Output Current                      | $I_{OH}$                  | -0.8           |                |      | A     | $V_{CC} - V_O = 15\text{V}$                     |      | 5    |
| Low Level Peak Output Current                       | $I_{OL}$                  | 0.8            |                |      | A     | $V_O - V_{EE} = 15\text{V}$                     |      | 5    |
| High Level Output Voltage                           | $V_{OH}$                  | $V_{CC} - 0.4$ | $V_{CC} - 0.2$ |      | V     | $I_O = -100\text{ mA}$ ,<br>$I_F = 9\text{ mA}$ | 1    | 6, 7 |
| High Level Output Voltage                           | $V_{OH}$                  |                | $V_{CC}$       |      | V     | $I_O = 0\text{ mA}$ ,<br>$I_F = 9\text{ mA}$    | 1    |      |
| Low Level Output Voltage                            | $V_{OL}$                  |                | 0.1            | 0.25 | V     | $I_O = 100\text{ mA}$                           | 2    |      |
| High Level Supply Current                           | $I_{CCH}$                 |                | 2.6            | 4.2  | mA    | $I_F = 9\text{ mA}$                             | 3, 4 |      |
| Low Level Supply Current                            | $I_{CCL}$                 |                | 2.6            | 4.2  | mA    | $V_F = 0\text{V}$                               |      |      |
| Threshold Input Current<br>Low to High              | $I_{FLH}$                 | 0.4            | 1.3            | 4.0  | mA    | $V_O > 5\text{V}$                               | 5, 6 |      |
| Threshold Input Voltage<br>High to Low              | $V_{FHL}$                 | 0.8            |                |      | V     |   |      |      |
| Input Forward Voltage                               | $V_F$                     | 1.2            | 1.55           | 1.95 | V     | $I_F = 9\text{ mA}$                             | 13   |      |
| Temperature Coefficient<br>of Input Forward Voltage | $\Delta V_F / \Delta T_A$ |                | -1.7           |      | mV/°C |   |      |      |
| Input Reverse Breakdown<br>Voltage                  | $BV_R$                    | 5              |                |      | V     | $I_R = 100\text{ }\mu\text{A}$                  |      |      |
| Input Capacitance                                   | $C_{IN}$                  |                | 70             |      | pF    | $f = 1\text{ MHz}$ , $V_F = 0\text{V}$          |      |      |
| UVLO Threshold                                      | $V_{UVLO+}$               | 12.1           | 13             | 13.9 | V     | $V_O > 5\text{V}$ , $I_F = 9\text{ mA}$         |      |      |
|   | $V_{UVLO-}$               | 11.1           | 12             | 12.9 |       |   |      |      |
| UVLO Hysteresis                                     | $UVLO_{HYS}$              | 0.5            | 1.0            |      | V     |   |      |      |

## Switching Specifications (AC)

All typical values are at  $T_A = 25^\circ\text{C}$ ,  $V_{CC} - V_{EE} = 15\text{V}$ ,  $V_{EE} = \text{Ground}$ . All minimum and maximum specifications are at recommended operating conditions ( $T_A = -40^\circ\text{C}$  to  $+105^\circ\text{C}$ ,  $I_{F(ON)} = 7\text{ mA}$  to  $11\text{ mA}$ ,  $V_{F(OFF)} = -3.6\text{V}$  to  $+0.8\text{V}$ ,  $V_{EE} = \text{Ground}$ ), unless otherwise noted.

| Parameter  | Symbol                         | Min. | Typ. | Max. | Unit              | Test Conditions   | Fig.               | Note  |        |
|--|--------------------------------|------|------|------|-------------------|---|--------------------|---|--------|
| Propagation Delay Time to High Output Level        | $t_{PLH}$                      | 30   | 55   | 110  | ns                | $R_g = 15\Omega$ ,<br>$C_g = 10\text{ nF}$ ,<br>$f = 20\text{ kHz}$ ,<br>Duty Cycle = 50%,<br>$V_{CC} = 15\text{V}$         | 7, 8, 9,<br>10, 11 |   |        |
| Propagation Delay Time to Low Output Level         | $t_{PHL}$                      | 30   | 55   | 110  | ns                |   |                    |   |        |
| Pulse Width Distortion                             | PWD                            |      | 0    | 40   | ns                |   |                    | 8   |        |
| Propagation Delay Difference Between Any Two Parts | PDD<br>( $t_{PHL} - t_{PLH}$ ) | -50  |      | +50  | ns                |   |                    | 16, 17  | 9      |
| Propagation Delay Skew                             | $t_{PSK}$                      |      |      | 50   | ns                |   |                    |   | 10     |
| Rise Time  | $t_R$                          |      | 8    | 28   | ns                | $C_g = 1\text{ nF}$ ,<br>$f = 20\text{ kHz}$ ,<br>Duty Cycle = 50%,<br>$V_{CC} = 15\text{V}$                                |                    |   |        |
| Fall Time  | $t_F$                          |      | 8    | 28   | ns                |   |                    |   |        |
| Output High Level Common Mode Transient Immunity   | $ CM_H $                       | 50   | 70   |      | kV/ $\mu\text{s}$ | $T_A = 25^\circ\text{C}$ , $I_F = 9\text{ mA}$ ,<br>$V_{CC} = 30\text{V}$ , $V_{CM} = 1500\text{V}$<br>with split resistors | 13                 | 11, 12  |        |
| Output Low Level Common Mode Transient Immunity    | $ CM_L $                       | 50   | 70   |      | kV/ $\mu\text{s}$ |   |                    | $T_A = 25^\circ\text{C}$ , $V_F = 0\text{V}$ ,<br>$V_{CC} = 30\text{V}$ , $V_{CM} = 1500\text{V}$<br>with split resistors | 11, 13 |

## Package Characteristics

All typical values are at  $T_A = 25^\circ\text{C}$ . All minimum/maximum specifications are at recommended operating conditions, unless otherwise noted.

| Parameter                                 | Symbol    | Device    | Min. | Typ.       | Max. | Unit               | Test Conditions  | Fig. | Note   |
|---|-----------|-----------|------|------------|------|--------------------|--|------|--------|
| Input-Output Momentary Withstand Voltage* | $V_{ISO}$ | ACPL-P347 | 3750 |            |      | $V_{RMS}$          | $RH < 50\%$ ,<br>$t = 1\text{ min.}$ ,<br>$T_A = 25^\circ\text{C}$ |      | 14, 16 |
|   |           | ACPL-W347 | 5000 |            |      | $V_{RMS}$          | $RH < 50\%$ ,<br>$t = 1\text{ min.}$ ,<br>$T_A = 25^\circ\text{C}$ |      | 15, 16 |
| Input-Output Resistance                   | $R_{I-O}$ |           |      | $>10^{14}$ |      | $\Omega$           | $V_{I-O} = 500\text{ V}_{DC}$                                      |      | 16     |
| Input-Output Capacitance                  | $C_{I-O}$ |           |      | 0.6        |      | pF                 | $f = 1\text{ MHz}$   |      |        |
| LED-to-Ambient Thermal Resistance         | $R_{11}$  |           |      | 135        |      | $^\circ\text{C/W}$ |  |      | 17     |
| LED-to-Detector Thermal Resistance        | $R_{12}$  |           |      | 27         |      |                    |  |      |        |
| Detector-to-LED Thermal Resistance        | $R_{21}$  |           |      | 39         |      |                    |  |      |        |
| Detector-to-Ambient Thermal Resistance    | $R_{22}$  |           |      | 47         |      |                    |  |      |        |

\* The Input-Output Momentary Withstand Voltage is a dielectric voltage rating that should not be interpreted as an input-output continuous voltage rating. For the continuous voltage rating, refer to your equipment level safety specification or Broadcom Application Note 1074 entitled "Optocoupler Input-Output Endurance Voltage."

## Notes:

1. Derate linearly above 85°C free-air temperature at a rate of 0.3 mA/°C.
2. Maximum pulse width = 10  $\mu$ s. This value is intended to allow for component tolerances for designs with I/O peak minimum = 1.0A. See applications section for additional details on limiting I<sub>OH</sub> peak.
3. Derate linearly above 85°C free-air temperature at a rate of 12.5 mW/°C .
4. Derate linearly above 85°C free-air temperature at a rate of 13.75 mW/°C . The maximum LED junction temperature should not exceed 125°C.
5. Maximum pulse width = 10  $\mu$ s.
6. In this test V<sub>OH</sub> is measured with a DC load current. When driving capacitive loads, V<sub>OH</sub> will approach V<sub>CC</sub> as I<sub>OH</sub> approaches zero amps.
7. Maximum pulse width = 1 ms.
8. Pulse Width Distortion (PWD) is defined as |t<sub>PHL</sub> - t<sub>PLH</sub>| for any given device.
9. Propagation Delay Difference (PDD) is the difference between t<sub>PHL</sub> and t<sub>PLH</sub> between any two units under the same test condition.
10. Propagation Delay Skew (t<sub>PSK</sub>) is the difference in t<sub>PHL</sub> or t<sub>PLH</sub> between any two units under the same test condition.
11. Pin 2 needs to be connected to LED common. Split resistor network in the ratio 1.5:1 with 232 $\Omega$  at the anode and 154 $\Omega$  at the cathode.
12. Common mode transient immunity in the high state is the maximum tolerable dV<sub>CM</sub>/dt of the common mode pulse, V<sub>CM</sub>, to assure that the output will remain in the high state (meaning, V<sub>O</sub> > 15.0V).
13. Common mode transient immunity in a low state is the maximum tolerable dV<sub>CM</sub>/dt of the common mode pulse, V<sub>CM</sub>, to assure that the output will remain in a low state (meaning, V<sub>O</sub> < 1.0V).
14. In accordance with UL1577, each optocoupler is proof tested by applying an insulation test voltage  $\geq 4500V_{RMS}$  for 1 second (leakage detection current limit, I<sub>I-O</sub>  $\leq 5 \mu$ A).
15. In accordance with UL1577, each optocoupler is proof tested by applying an insulation test voltage  $\geq 6000V_{RMS}$  for 1 second (leakage detection current limit I<sub>I-O</sub>  $\leq 5 \mu$ A).
16. Device considered a two-terminal device: pins 1, 2, and 3 shorted together and pins 4, 5, and 6 shorted together.
17. The device was mounted on a high conductivity test board as per JEDEC 51-7.

# Typical Performance Plots

Figure 1  $V_{OH}$  vs. Temperature




Figure 2  $V_{OL}$  vs. Temperature




Figure 3  $I_{CC}$  vs. Temperature




Figure 4  $I_{CC}$  vs.  $V_{CC}$




Figure 5  $I_{FLH}$  Hysteresis




Figure 6  $I_{FLH}$  vs. Temperature




Figure 7 Propagation Delay vs.  $V_{CC}$




Figure 8 Propagation Delay vs.  $I_F$




Figure 9 Propagation Delay vs. Temperature




Figure 10 Propagation Delay vs.  $R_g$




Figure 11 Propagation Delay vs.  $C_g$






Figure 12 Input Current vs. Forward Voltage



**Figure 13 CMR Test Circuit with Split Resistors Network and Waveforms**



## Application Information

### Product Overview Description


The ACPL-P347/W347 is an optically isolated power output stage capable of driving power or SiC. Based on BCDMOS technology, this gate drive optocoupler delivers higher peak output current, better rail-to-rail output voltage performance and two times faster speed than the previous generation products.

The high peak output current and short propagation delay are needed for fast MOSFET switching to reduce dead time and improve system overall efficiency. Rail-to-rail output voltage ensures that the MOSFET's gate voltage is driven to the optimum intended level with no power loss across the MOSFET. This helps the designer lower the system power which is suitable for bootstrap power supply operation.

It has very high CMR (common mode rejection) rating which allows the microcontroller and the MOSFET to operate at very large common mode noise found in industrial motor drives and other power switching applications. The input is driven by direct LED current and has a hysteresis that prevents output oscillation if insufficient LED driving current is applied. This eliminates the need of additional Schmitt trigger circuit at the input LED.

The stretched SO6 package which is up to 50% smaller than conventional DIP package facilitates smaller and more compact design. These stretched packages are compliant to many industrial safety standards such as IEC/EN/DIN EN 60747-5-5, UL 1577, and CSA.

**Figure 14 Recommended Application Circuit with Split Resistors LED**



### Recommended Application Circuit

The recommended application circuit shown in Figure 14 illustrates a typical gate drive implementation using the ACPL-P347.

The supply bypass capacitors (1 μF) provide the large transient currents necessary during a switching transition. Because of the transient nature of the charging currents, a low current (4.0 mA) power supply will be enough to power the device. The split resistors (in the ratio of 1.5:1) across the LED will provide a high CMR response by providing a balanced resistance network across the LED.

The gate resistor  $R_G$  serves to limit gate charge current and controls the MOSFET switching times.

In PC board design, care should be taken to avoid routing the MOSFET drain or source traces close to the ACPL-P347 input as this can result in unwanted coupling of transient signals into ACPL-P347 and degrade performance.



## LED Current Input with Hysteresis

The detector has optical receiver input stage with built in Schmitt trigger to provide logic compatible waveforms, eliminating the need for additional wave shaping. The hysteresis (Figure 12) provides differential mode noise immunity and minimizes the potential for output signal chatter.

## Thermal Model for ACPL-P347/W347 Stretched SO6 Package Optocoupler

### Definitions

$R_{11}$ : Junction to Ambient Thermal Resistance of LED due to heating of LED

$R_{12}$ : Junction to Ambient Thermal Resistance of LED due to heating of Detector (Output IC)

$R_{21}$ : Junction to Ambient Thermal Resistance of Detector (Output IC) due to heating of LED.

$R_{22}$ : Junction to Ambient Thermal Resistance of Detector (Output IC) due to heating of Detector (Output IC).

$P_1$ : Power dissipation of LED (W).

$P_2$ : Power dissipation of Detector/Output IC (W).

$T_1$ : Junction temperature of LED (°C).

$T_2$ : Junction temperature of Detector (°C).

$T_A$ : Ambient temperature.

Ambient Temperature: Junction to Ambient Thermal Resistances were measured approximately 1.25 cm above optocoupler at ~23°C in still air.

| Thermal Resistance | °C/W |
|--------------------|------|
| $R_{11}$           | 135  |
| $R_{12}$           | 27   |
| $R_{21}$           | 39   |
| $R_{22}$           | 47   |

This thermal model assumes that an 6-pin single-channel plastic package optocoupler is soldered into a 7.62 cm × 7.62 cm printed circuit board (PCB) per JEDEC standards. The temperature at the LED and Detector junctions of the optocoupler can be calculated using the equations below.

$$T_1 = (R_{11} \times P_1 + R_{12} \times P_2) + T_A \quad (1)$$

$$T_2 = (R_{21} \times P_1 + R_{22} \times P_2) + T_A \quad (2)$$

Using the given thermal resistances and thermal model formula in this datasheet, we can calculate the junction temperature for both LED and the output detector. Both junction temperatures should be within the absolute maximum rating.

For example, given  $P_1 = 17$  mW,  $P_2 = 124$  mW,  $T_A = 85^\circ\text{C}$ :

LED junction temperature,

$$\begin{aligned} T_1 &= (R_{11} \times P_1 + R_{12} \times P_2) + T_A \\ &= (135 \times 0.017 + 27 \times 0.124) + 85 \\ &= 90.7^\circ\text{C} \end{aligned}$$

Output IC junction temperature,

$$\begin{aligned} T_2 &= (R_{21} \times P_1 + R_{22} \times P_2) + T_A \\ &= (39 \times 0.017 + 47 \times 0.124) + 85 \\ &= 91.5^\circ\text{C} \end{aligned}$$

$T_1$  and  $T_2$  should be limited to 125°C based on the board layout and part placement.

## Related Documents

|             |                       |  |
|-------------|-----------------------|--|
| AV02-0421EN | Application Note 5336 | Gate Drive Optocoupler Basic Design for IGBT/MOSFET        |
| AV02-3698EN | Application Note 1043 | Common-Mode Noise: Sources and Solutions                   |
| AV02-0310EN | Reliability Data      | Plastics Optocouplers Product ESD and Moisture Sensitivity |

---

For product information and a complete list of distributors, please go to our web site:  
[www.broadcom.com](http://www.broadcom.com).



Broadcom, the pulse logo, Connecting everything, Avago Technologies, Avago, the A logo, and R<sup>2</sup>Coupler are among the trademarks of Broadcom and/or its affiliates in the United States, certain other countries and/or the EU.

Broadcom Proprietary and Confidential. Copyright © 2017 Broadcom. All Rights Reserved. The term "Broadcom" refers to Broadcom Limited and/or its subsidiaries.

Broadcom reserves the right to make changes without further notice to any products or data herein to improve reliability, function, or design. Information furnished by Broadcom is believed to be accurate and reliable. However, Broadcom does not assume any liability arising out of the application or use of this information, nor the application or use of any product or circuit described herein, neither does it convey any license under its patent rights nor the rights of others.  
AV02-4748EN – April 26, 2017