

Contact insert module - HC-M-DSUB 09-UT-F - 1417307

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Contact insert module, Number of positions: 9, Type: D-SUB-9, Socket, Screw connection, 50 V, 1 A, 0.08 mm² ... 0.5 mm², Application: Data



Key Commercial Data

Packing unit	1 STK
GTIN	
GTIN	4055626112497

Technical data

Dimensions

Height	35.7 mm
Width	34.2 mm
Length	14.6 mm

Electrical characteristics

Note	For HEAVYCON housing type B6 to B48, HC-M-B...MF... module carrier frame required
Rated voltage (III/3)	50 V
Rated current	1 A
Rated surge voltage	0.8 kV
Connection profile	9

Ambient conditions

Ambient temperature (operation)	-40 °C ... 125 °C
---------------------------------	-------------------

Mechanical characteristics

Conductor cross section	0.08 mm² ... 0.5 mm²
Connection cross section AWG	28 ... 20
Stripping length of the individual wire	4.2 mm
Tightening torque	0.03 Nm ... 0.05 Nm

Contact insert module - HC-M-DSUB 09-UT-F - 1417307

Technical data

Mechanical characteristics

Insertion/withdrawal cycles	≥ 500
Minimum housing height	72 mm

General

Type	D-SUB-9
Series	HC-M-DSUB
Color	light gray
Number of module slots	1
Connection method	Screw connection
Flammability rating according to UL 94	V0
Degree of pollution	3
Overvoltage category	III

Material data

Contact material	Copper alloy
Contact surface material	Ag
Contact carrier material	PC

Standards and Regulations

Flammability rating according to UL 94	V0
--	----

Approvals


Approvals

Approvals

EAC

Ex Approvals

Approval details

EAC		EAC-Zulassung
-----	---	---------------

Phoenix Contact 2017 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>