1801 Morgan Street Rockford, Illinois 61102 800-435-2931 www.molexkits.com



## **Datasheet for 76650-0159**

## **General Information**

**Part Number:** 76650-0159

Manufacturer: Molex / Waldom

Title: Micro-Fit 3.0 Power Connector Kit

**Description:** 3.00mm (.118") Pitch Single Row Free Hanging Plug and Receptacle

**Product Family:** Micro-Fit 3.0™

Certificates: (Molex Parts within this kit) - EU RoHS Compliant, UL, CSA and TUV

Country of Origin: Kit assembled in U.S.A.

## **Specifications**

Design

Configuration: Wire-to-Wire

Pitch: 3.0mm (.118")

Connector Type: Receptacles and Plugs

**Circuit Sizes:** 2, 3, 4, 5 and 6

Current Rating: 5 Amps
Voltage: 250 Volts

Wire size: (30-26) and (24-20) AWG

# **Product Highlights**

The Micro-Fit 3.0 is a unique interconnect system designed to meet the need for a high contact density signal or power connector and incorporates many of the features previously found on larger power connectors. These 3.00mm (.118") pitch connectors are the perfect choice when you need compact connectors that carry up to 5 amperes of current. Micro-Fit products are available in more circuit sizes, and dual row, and wire-to-board applications. The product family has over 500 part numbers.



#### **Datasheet for 76650-0159**

#### **Features and Benefits**

- Fully isolated contacts
- Fully polarized to mate, prevents accidental mismating
- Integral pull tabs for ease in unmating
- Positive latching to mate, prevents accidental disconnects
- Box-type spring contact for high normal force
- · Locking tang secures terminal in housing
- 4 points of contact for optimum reliability

## **Applications**

- Personal Computers
- Computers and Workstations
- Handheld Devices
- Office Equipment
- Fan Tray Assemblies
- Power Supplies
- · Gaming and Vending

## Bill of Materials for Part No. 76650-0159

| Molex Part No. | Country of Origin | Description   | Quantity in<br>Kit |
|----------------|-------------------|---|--------------------|
| 43030-0007-C   | USA               | Female Crimp Terminal Micro-Fit 24-20 AWG               | 100                |
| 43031-0007-C   | USA               | Male Crimp Terminal Micro-Fit 24-20 AWG                 | 100                |
| 43030-0010-C   | USA               | Female Crimp Terminal Micro-Fit 30-26 AWG               | 100                |
| 43031-0010-C   | USA               | Male Crimp Terminal Micro-Fit 30-26 AWG                 | 100                |
| 43645-0200     | USA               | 3.0mm (.118") Pitch Micro-Fit 3.0™ Receptacle 2 Circuit | 25                 |
| 43645-0300     | USA               | 3.0mm (.118") Pitch Micro-Fit 3.0™ Receptacle 3 Circuit | 25                 |
| 43645-0400     | USA               | 3.0mm (.118") Pitch Micro-Fit 3.0™ Receptacle 4 Circuit | 15                 |
| 43645-0500     | USA               | 3.0mm (.118") Pitch Micro-Fit 3.0™ Receptacle 5 Circuit | 10                 |
| 43645-0600     | USA               | 3.0mm (.118") Pitch Micro-Fit 3.0™ Receptacle 6 Circuit | 5                  |
| 43640-0201     | Singapore         | 3.0mm (.118") Pitch Micro-Fit 3.0™ Plug 2 Circuit       | 25                 |
| 43640-0301     | Singapore         | 3.0mm (.118") Pitch Micro-Fit 3.0™ Plug 3 Circuit       | 25                 |
| 43640-0401     | Singapore         | 3.0mm (.118") Pitch Micro-Fit 3.0™ Plug 4 Circuit       | 15                 |
| 43640-0501     | Singapore         | 3.0mm (.118") Pitch Micro-Fit 3.0™ Plug 5 Circuit       | 10                 |
| 43640-0601     | Singapore         | 3.0mm (.118") Pitch Micro-Fit 3.0™ Plug 6 Circuit       | 5                  |

## Recommended Molex Tool(s) for Part No. 76650-0159\*

#### Country

| Molex Part No. | of Origin | Description     |
|----------------|-----------|-----------------|
| 63819-0000 *   | Sweden    | Hand Crimp Tool |
| 11-03-0043 *   | USA       | Extraction Tool |

<sup>\*</sup>Tool(s) not included in kit. Tool(s) ordered separately.