






PRODUCT NUMBER	PITCH
OQxx15x000J0G	3.50 mm



Material:

- Item ③ Male contact pin: Copper ,Tin plated
- Item ④ Terminal housing: Thermoplastic (UL94V-0)
- Item ⑤ Flange nut: Brass M2.5

Electrical:

- Voltage rating: 300V/300V
- Current rating: 10A/10.5A
- Withstanding Voltage: 1.6 KV/2.5KV
- Operating temperature: -40°C to +115°C
- Soldering temperature: 260°C±5°C/5 Sec
- Safety Approval:

DIMENSION

Dim A	(N-1)×3.5+13.8
Dim B&C	(N-1)×3.5
Dim D	(N-1)×3.5+8.6

N= Number of poles

Poles	Tol
2p-6p	±0.15
7p-12p	±0.20
13p-16p	±0.25
17p-24p	±0.30

PART NO.: OQ xx 1 5 x 0 00J0 G

No. of poles	02 2 poles	02 2 poles	2 Black (RAL9005)	RoHS compliant (lead<4%) In copper Alloy
	03 3 poles	03 3 poles	2 Red (RAL3001/D)	
	...	03 3 poles	3 Orange(RAL2011/P)	
	24 24 poles	04 4 poles	4 Yellow(RAL1018/A)	
		05 5 poles	5 Green(RAL6018/T)	
		06 6 poles	6 Blue (RAL5015/A)	
		08 8 poles	8 Grey(RAL7035/D)	
		09 9 poles	9 White(RAL1102)	
		10 10 poles	C Green(RAL6018/U)	

mat'l. code	surface ASME Y14.5	tolerance ASME Y14.5	projection	product family
ltr	ecn	no	dr	date
			angles	tolerances unless otherwise specified
			X°±1°	X.XX±0.1
			dr	HANKE FENG 032614
			engr	HANKE FENG 032614
			chr	SHI JUN 032614
			appd	SHI JUN 032614
sheet index	revision	A		sheet 1 of 1
	sheet	1		size A4
				type CUSTOMER Drawing