APPLICA	BLE STAN	DARD								
	OPERATING TEMPERATURE RANGE		-35°C TO +85°C(NO	TE 1)		MPERATURE RANGE		-10°C TO +60°C		
RATING VOLTAGE		30V AC			APPLICABLE CONNECTOR			DF40*-**DS-0. 4V (**)		
CURREN			0. 3A	0. 3A						
			SPECI	FICA	TIONS	S				
ITEM			TEST METHOD				REQU	IREMENTS	QT	АТ
	RUCTION	T. ((a)	/ AND DV ME ASUBING INCTES		Lago	2000INO	FO DD	AVAUNIO	1	1
GENERAL EX	AMINATION		VISUALLY AND BY MEASURING INSTRUMENT. CONFIRMED VISUALLY.			CORDING T	IO DR	AWING.	X	X
ELECTRIC CHARAC									1^	1^
		20mV AC OR LESS 1khz,1m A .				180mΩ MAX.				1_
INSULATION RESISTANCE		100V DC.			50M	50MΩ MIN.			X	<u> </u>
VOLTAGE PROOF		100V AC FOR 1 min.			NO	NO FLASHOVER OR BREAKDOWN.				1_
MECHAI	NICAL CHA	RACTI	ERISTICS						X	1
MECHANICAL OPERATION		3000TIMES INSERTIONS AND EXTRACTIONS.			2 1	① CONTACT RESISTANCE: 180mΩ MAX.② NO DAMAGE, CRACK OR LOOSENESS OF PARTS.				_
COUN	IT DI	ESCRIPTI	ON OF REVISIONS		DESIGNED)		CHECKED	D/	ATE
REMARKS								VII TIVED	11 00 01	
NOTE1: INCLUDE THE TEMPERATURE						APPROVE CHECKED DESIGNED		KH. IKEDA TS. MIYAZAKI	11. 08. 01	
								YH. MICHIDA	11. 07. 27	
Unless otherwise specified, refer			r to JIS C 5402.			DRAWN		YH. MICHIDA	11. 07. 27	
Note QT:Qualification Test AT:Assurance Test X:Applicable Test DF					DRAW	AWING NO. ELC4-315630-53				
HS.	SI	SPECIFICATION SHEET			PART NO.		DF40JC-*DP-0. 4V (53)			
	HIR	HIROSE ELECTRIC CO., LTD.			CODE NO	E NO. CL684		Δ	1/1	