

- 1. P1. CONNECTOR: NORCOMP MICRO D 9S, ASSEMBLED HOOD W/THUMBSCREWS
- 2. P2. BLUNT CUT END

DESCRIPTION: 9 POS MICRO-D FEMALE (ASSEMBLED) TO BLUNT CUT

- 3. WIRE: 28AWG [7X36] x9C +ALUMINUM FOIL W/ BRAID 65%, UL2464+CSA, COLOR BLACK
- 4. PINDUT:

P1	P2
1	BLACK
2 ———	BR□WN
3 —	RFD
4	——————————————————————————————————————
4 ———	
5 ———	YELLOW
6 ———	GREEN
7 —	BLUE
8 —	VIOLET
9 —	——GRAY
SHFLL	——SHIFL D
STILL	3111

CCA-009-YYYR152 = INCHES — LENGTH F = FEETM = METERS

EXAMPLES:

CCA-009-I18R152 = 18 INCHESCCA-009-F03R152 = 3 FEETCCA-009-M01R152 = 1 METER

PACKAGED: 1 PER BAG

ROHS COMPLIANT

Ø	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF NorComp AND SHALL NOT BE REPRODUCED, COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.	CHECKED:
		SCALE:

CHECKED: DATE: SCALE: SHEET NTS 1 1 DWG NO.

CCA-009-YYYR152

DATE:

01-18-12

OF

REV

2

_				-
N	r	$\sim$	m	•
IN		JU	m	١