



Article Number: 170-03024

Description: Braided Sleeving, Split Wrap, .5" Dia, PET, Black, 75 ft/reel

Base Data		
	Local Order Number	170-03024
	Туре	BSPSW120
	Color	Black (BK)
	Features and Benefits	<ul> <li>Split wrap design installs quickly, saving assembly time and future accessibility without disassembly.</li> <li>Unique construction retains shape and rigidity throughout unrolling.</li> <li>Easy open design allows quick assembly, future access, and ability to apply protective sleeving post assembly or post installation situations.</li> </ul>
	Quantity Per	reel
	Product Description	A lateral split, semi-rigid and flame retardant braided sleeving configuration used when ease of installation and repeat access to wire bundle is required. The lateral split allows the sleeving to open and accommodate a variety of bundling requirements. The 25% edge overlap rolls back over connectors and splices without exposing the bundled wires.
	Short Description	Braided Sleeving, Split Wrap, .5" Dia, PET, Black, 75 ft/reel
Product Dimensions		
	Length L (Imperial)	75.0ft
	Length L (Metric)	22.9m
	Reel Length (imperial)	75.0ft
	Bundle Diameter Max. (Imperial)	0.5"
	Bundle Diameter Max. (Metric)	12.7mm
	Nominal Diameter (Imperial)	1/2"
	Nominal Diameter (Metric)	12.7mm
Material and Specifications		
	Material	Polyester (PET)
	Material Shortcut	PET
	Flammability	UL 94 V0
	Operating Temperature	-94°F to +248°F (-70°C to +125°C)

generated on: 4/28/2017

## 170-03024



Material and Specifications	ROHS Compliant	Yes
	UL Recognized (US and Canada)	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	75ft
	Package Quantity (Metric)	22.86m
	Customs Number(Schedule B)	3926909987
	Weight (imperial)	1.05lbs
	Weight (Metric)	0.48kg

generated on: 4/28/2017