SMT Trimmer Potentiometers

Discontinued

3 mm Square SMT Trimmer Potentiometers with the rotation stopper (Cermet, Open Frame Type)



Type: **EVM3V**

 Planed final production : March.2019


Features

- Rotation stopper featured type
- Automatic adjustment type
- High reliability realized by cermet element
- Excellent mountability
- Conforms to JIS C5260-1:1999
- RoHS compliant

Recommended Applications

- Audio/visual, office, and communication equipment
- General electronic equipment

Explanation of Part Numbers



Example : B52=500 Ω

| Specifications | | |
|--|------------------------------------|--|
| Total Resistance Value Resistance Tolerance | 100 Ω to 1 M Ω ±25 % | |
| Power Rating Limiting Element Voltage | 0.15 W 50 V | |
| Rotation Torque | 2 to 10 mN·m | |
| Stopper Strength | 15 mN·m min. | |
| Temperature Coefficient of Resistance | ±250 × 10 ⁻⁶ /°C | |

Minimum Quantity/Packing Unit

| Part Number | Taping | | |
|-------------|-------------------|--------------------|-------------------|
| Fait Number | Quantity per reel | Packaging quantity | Dia. of reel (mm) |
| EVM3V | 2,000 | 10,000 | φ178 |

The standard packaging methods for a reel is ϕ 178. Please contact us, if you would like different packaging methods. (Bulk, Reel of ϕ 330, Reel of ϕ 380)

Dimensions in mm (not to scale)

3-terminal, for Automatic Trimming Adjustment

