

SAW Components

Data Sheet R 724





SAW Components	R 724
Resonator	403,966 MHz

Data Sheet


Features

- 1-port resonator
- Provides reliable, fundamental mode, quartz frequency stabilization i.e. in transmitters or local oscillators

Terminals

Ni, gold plated


Ceramic package QCC8C



Dimensions in mm, approx. weight 0,1 g

Pin configuration

InputGroundGround (case)



Туре	Ordering code	Marking and Package	Packing		
		according to	according to		
R 724	B39401-R 724-U310	C61157-A7-A56	F61074-V8070-Z000		

Electrostatic Sensitive Device (ESD)

Maximum ratings

Operable temperature range	T_{A}	- 45/+ 85	°C	
Storage temperature range	$T_{\rm stg}$	- 45/+ 85	°C	
DC voltage	$V_{\rm DC}$	12	V	between any terminals
Source power	P_{s}	0	dBm	



SAW Components R 724

Resonator 403,966 MHz

Data Sheet

Characteristics

Reference temperature: $T_{\rm A}=25\,^{\circ}{\rm C}$ Terminating source impedance: $Z_{\rm S}=50\,\Omega$ Terminating load impedance: $Z_{\rm L}=50\,\Omega$

		min.	typ.	max.	
Center frequency 1)	$f_{\rm C}$	403,891	403,966	404,041	MHz
Minimum insertion attenuation			1.1	2.0	40
	$lpha_{\sf min}$	_	1,4	2,0	dB
Unloaded quality factor	Q_{U}	7500	12900	_	
Ageing of f _c		_	_	± 50	ppm
Equivalent circuit elements					
Motional capacitance	C_1	_	1,710	_	fF
Motional inductance	L_1	_	90,77	_	μΗ
Motional resistance	R_1	_	17	27	Ω
Parallel capacitance	C_0	_	2,6	_	pF
Temperature coefficient of frequency 2)	TC _f	_	- 0,032	_	ppm/K ²
Turnover temperature	T_{0}	10	_	40	°C

¹⁾ Center frequency is defined as maximum of the real part of the admittance

²⁾Temperature dependence of f_c : $f_c(T_A) = f_c(T_0)(1 + TC_f(T_A - T_0)^2)$



SAW Components R 724
Resonator 403,966 MHz

Data Sheet

Published by EPCOS AG Surface Acoustic Wave Components Division, OFW E UE P.O. Box 80 17 09, D-81617 München

© EPCOS AG 1999. All Rights Reserved.

As far as patents or other rights of third parties are concerned, liability is only assumed for components per se, not for applications, processes and circuits implemented within components or assemblies.

The information describes the type of component and shall not be considered as assured characteristics.

Terms of delivery and rights to change design reserved.

For questions on technology, prices and delivery please contact the sales offices of EPCOS AG or the international representatives.

Due to technical requirements components may contain dangerous substances. For information on the type in question please also contact one of our sales offices.