APPLICA	BLE STAN	DARD								
OPERATING TEMPERATURI		RE RANGE	$_{RANGE}$ -35° C TO $+85^{\circ}$ C (NOTE 1) $_{TEN}$			TURE RANGE -10° C TO $+60^{\circ}$ C				
RATING	VOLTAGE		00// 10/00		APPLICABLE CONNECTOR		DF40*-50DS-0. 4V (**)			
CURRENT		0. 3A								
			SPECI	FICAT	IONS					
	EM		TEST METHOD			REQU	JIREMENTS	QT	АТ	
CONSTRUCTION					T	ACCORDING TO DRAWING. X X				
GENERAL EXAMINATION		VISUALLY AND BY MEASURING INSTRUMENT.			ACCOF	ACCORDING TO DRAWING.			X	
MARKING		CONFIRMED VISUALLY.						X	X	
		ACTERISTICS 20mV AC OR LESS 1khz,1m A . 180mΩ MAX.							1	
		·								
INSULATION RESISTANCE		100V DC.			50MΩ I	50MΩ MIN.			-	
VOLTAGE PROOF		100V AC FOR 1 min.			NO FLA	NO FLASHOVER OR BREAKDOWN.			-	
MECHAN	NICAL CHA	ARACTI	ERISTICS		·					
MECHANICAL OPERATION		3000TIMES INSERTIONS AND EXTRACTIONS.			② NO	① CONTACT RESISTANCE: 180mΩ MAX. ② NO DAMAGE, CRACK OR LOOSENESS OF PARTS.			_	
COUN	T D	ESCRIPTI	ON OF REVISIONS	D	ESIGNED		CHECKED	DA	ATE.	
A 5000							020112	"		
REMARKS						APPROVED	KH. IKEDA	12.0)1. 17	
NOTE1: INCL	UDE THE TEMP	ERATURE RISING BY CURRENT				CHECKED	TS. MIYAZAKI	12.01.17		
Unless other	erwise speci	fied, refer	ed. refer to JIS C 5402.			DESIGNED	TR. YUNOK I		12.01.16	
Unless otherwise specified, refer to JIS C 5402. Note QT:Qualification Test AT:Assurance Test X:Applicable Test							TR. YUNOKI ELC4-31564	R. YUNOKI 12. 01. 16 LC4-315646-01		
					ART NO.					
		OSE ELECTRIC CO., LTD.			ODE NO.	o. CL684-4072-6-53		Δ	1/1	