


**Specifications:**

Sound level Category	Medium Sound Level
Mode of Operation	Fast Pulse
Mounting	Printed Circuit Board (see note B)
Voltage Rating	6 - 16 Vdc
Frequency	2900 Hz ±500 Hz
Loudness (Min. Voltage)	68 dB(A) min. @ 2 FT and 6 Vdc
Loudness (Max Voltage)	78 dB(A) min. @ 2FT and 16 Vdc
Current Draw	3 mA Max @ 6 Vdc
Current Draw	12 mA Max @ 16 Vdc
Min Pulse Rate (PPS)	2 @ 6 Vdc
Max Pulse Rate (PPS)	10 @ 16 Vdc
Duty Cycle (%)	50 (Approx)
Storage Temperature	-40°C to +85°C
Operating Temperature	-30°C to +65°C
Weight (Typical)	0.6 oz (17 g)
Housing	6/6 Nylon, Color Black
Options	For other options contact factory

**Dimensions:** Inches (mm)

**ROHS Compliant**



NOTE A:  
 TERMINALS - .031" DIA. TIN PLATED NICKEL. TERMINAL  
 1 IS POSITIVE, TERMINAL 3 IS NEGATIVE. TERMINAL  
 2 IS FOR SUPPORT ONLY - NO ELECTRICAL  
 CONNECTION.

NOTE B:  
 MOUNTING - INSERT INTO PRINTED CIRCUIT  
 BOARD AND HAND OR MACHINE SOLDER.