APPLICA	BLE STAN	DARD										
	OPERATING TEMPERATUR	E RANGE	1 0 0 0 0 0 0 0 0 0			RAGE PERATURE RANGE			-10°C TO 60°C			
RATING VOLTAGE			30V AC			LICABLE			DF40*-20DS-0. 4V			
CURRENT		0. 3A										
	1		SPEC	IFICA	ATION	NS		<u> </u>				
ľ	ГЕМ		TEST METHOD				F	REQUI	REMENTS	QT	AT	
CONSTR	RUCTION	•								'		
GENERAL EX	AMINATION	VISUALLY AND BY MEASURING INSTRUMENT.				ACCOF	RDING T	O DR	AWING.	Х	Х	
MARKING	10 01 14 D 4	CONFIRMED VISUALLY.								X	X	
		CTERISTICS 20mV AC OR LESS 1khz,1m A .				100~0	NAAV					
						180mΩ MAX.				X	_	
INSULATIO RESISTANO		100V DC.				50MΩ MIN.				Х	_	
VOLTAGE F		100V AC FOR 1 min.				NO FLASHOVER OR BREAKDOWN.				X		
		 									_	
MECHANIC			ES INSERTIONS AND EXT	RACTIO	NS (1 00	NTACTI	DESIS	TANCE: 180mQ MAX	,		
OPERATIO		SUCCINICION SAND EXTRACTIONS.				 CONTACT RESISTANCE: 180mΩ MAX. NO DAMAGE, CRACK OR LOOSENESS OF PARTS. 					_	
COUN	IT DE	SCRIPTIO	ON OF REVISIONS		DESIG	NED			CHECKED	DA	ATE	
Δ												
REMARKS NOTE1: INCLUDE THE TEMPERATURE Unless otherwise specified, refe			AATURE RISING BY CURRENT d, refer to JIS C 5402, IEC 60512.			-	APPROVED CHECKED DESIGNED DRAWN		MO. ISHIDA		7. 17	
						-			TS. MIYAZAKI		15. 07. 17 15. 07. 17	
						-			SH. HOSODA KR. AJITO)7. 1 <i>7</i>)7. 17	
Note QT:Qualification Test AT:Assurance Test X:Applicable					DR				ELC-315642-	_		
ЖS	SF	PECIFICATION SHEET			PART	RT NO. DF			40JC-20DP-0. 4V (53)			
11.7					CODE	E NO. CL68		_684	4-4068-9-53		1/1	