


Top of Cabinet Air Sealing Accessories

Designed for the Net-Access™ and Net-SERV™ Cabinets, innovative air sealing accessories prevent cooling air from escaping through cable inlets improving thermal efficiency of the cabinets. Air sealing accessories snap into the cabinet top knock-outs for fast configuration.

600 mm (24") Net-SERV™ Cabinet shown with optional vertical exhaust duct.



Cool Boot® Cabinet Top Air Sealing Fitting is used to seal copper data cables entering the cabinet.



Net-SERV™ Cabinets are provided with four pre-installed 3"x 8" and two 3"x 5" cabinet top covers and cable protection bezels.



Cabinet Top Air Sealing Fiber Optic Fitting is used to provide a transition and seal for fiber optic cables entering the cabinet via slit corrugated tubing.



Cabinet Top Cover and Cable Protection Bezel are used when additional knock-outs are removed from the cabinet.



Part Number	Part Description	Std. Pkg. Qty.
-------------	------------------	----------------

Cool Boot® Cabinet Top Air Sealing Fitting

CTG3X8	Used to seal off 3" x 8" cabinet top openings when cables are routed through the top of a cabinet. Airtight fabric and Ultra-Cinch™ Tie closes top of fabric, minimizing hot air bypass around cables to improve cooling of network equipment and reduce energy costs. For use with both Net-SERV™ and Net-Access™ Cabinets. Requires cabinet top cable protection bezel to be installed.	1
---------------	---	---



Cabinet Top Air Sealing Fiber Optic Fitting

CTIDT15	Used to transition 1.5" (38mm) diameter slit corrugated tubing directly into a 3" x 8" or 3" x 5" cabinet top opening. Split design allows easy access to add or remove cables. Fitting minimizes hot air bypass around tubing to improve cooling of network equipment and reduce energy costs. For use with both Net-SERV™ and Net-Access™ Cabinets. Requires cabinet top cable protection bezel to be installed.	1
----------------	--	---



Cabinet Top Cover and Cable Protection Bezel

CTCC3X8	Used to seal off 3" x 8" cabinet top openings after knock-outs are removed. Can also be used to add the CTG3X8 or CTIDT15 to openings where knock-out has been removed. For use with both Net-SERV™ and Net-Access™ Cabinets.	1
----------------	---	---



Slit Corrugated Loom Tubing

CLT150F-X3*	Provides a vertical pathway as cables transfer from the FiberRunner® Fitting to the equipment below. Inside diameter is 1.48" (37.6mm) and outside diameter 1.73" (43.9mm). Sold in 10' rolls.	1
--------------------	--	---

*For other colors replace suffix X3 (Orange) with X4 (Yellow) or X20 (Black).