# HellermannTyton

| | |
|---|---|
| Article Number: | 556-00169 |
| Description: | Thermal Transfer Ribbon, 4.33" x 242', .50" Core, PET, Black, 1/pkg |

| Base Data | | |
|---|---|---|
| | Local Order Number | TT100OUTSM |
| | Type | TT100OUTSM |
| | Color | Black (BK) |
| | Features and benefits | • Ribbons are resin based for the best print durability.<br>• Ribbons are available to fit all HellermannTyton printers for easy resupply.<br>• Ribbons are available in colors for maximizing design printing capabilities.<br>• Ribbons meet UL recognition and Military standard where applicable to meet specific industry label requirements. |
| | Quantity Per | pieces |
| | Product Description | HellermannTyton thermal transfer ribbons are designed for use in HellermannTyton thermal transfer printers.  Available on 1/2" and 1" cores, the ribbons are coated side out and available in two different lengths.  All ribbons are available in a variety of colors and are matched to the HellermannTyton label stock to give the best chemical and abrasion resistance. |
| | Short Description | Thermal Transfer Ribbon, 4.33" x 242', .50" Core, PET, Black, 1/pkg |
| Product Dimensions | | |
| | Length L (Imperial) | 242.0ft |
| | Length L (Metric) | 74.0m |
| | Reel Length (imperial) | 242.0ft |
| | Variant | Colored ribbon |
| | Width W (Imperial) | 4.33" |
| | Width W (Metric) | 110.0mm |
| | Print Method | Thermal transfer |
| Material and Specifications | | |
| | Material | Polyester Film |
| | Material Shortcut | PET |
| | Operating Temperature | +40°F to +300°F (+4°C to +82°C) |
| | ROHS Compliant | Yes |

| Material and Specifications | Certification/Specification | UL-Recognized |
|---|---|---|
| Logistic and Packaging | | |
| | Package Quantity (Imperial) | 1 |
| | Package Quantity (Metric) | 1 |
| | Customs Number(Schedule B) | 9612101000 |
| | Weight (imperial) | 0.662lbs |
| | Weight (Metric) | 0.15kg |