

COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE	COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE		
△					△						
△					△						
<b>APPLICABLE STANDARD</b>											
<b>RATING</b>	OPERATING TEMPERATURE RANGE	-30 °C TO 85 °C(NOTE 1)			STORAGE TEMPERATURE RANGE	-10°C TO 60 °C					
	VOLTAGE	250V AC			CURRENT	3A					
<b>SPECIFICATIONS</b>											
<b>ITEM</b>		<b>TEST METHOD</b>			<b>REQUIREMENTS</b>			<b>QT</b>	<b>AT</b>		
<b>CONSTRUCTION</b>											
GENERAL EXAMINATION		VISUALLY AND BY MEASURING INSTRUMENT.			ACCORDING TO DRAWING.			×	×		
MARKING		CONFIRMED VISUALLY.						×	×		
<b>ELECTRIC CHARACTERISTICS</b>											
CONTACT RESISTANCE		100 mA (DC OR 1000 Hz).			30 mΩ MAX.			×	—		
INSULATION RESISTANCE		500V DC.			1000 MΩ MIN.			×	—		
VOLTAGE PROOF		650 V AC FOR 1 min.			NO FLASHOVER OR BREAKDOWN.			×	—		
<b>MECHANICAL CHARACTERISTICS</b>											
MECHANICAL OPERATION		30 TIMES INSERTIONS AND EXTRACTIONS.			① CONTACT RESISTANCE: 30 mΩ MAX. ② NO DAMAGE, CRACK AND LOOSENESS, OF PARTS.			×	—		
VIBRATION		FREQUENCY 10 TO 55 Hz, SINGLE AMPLITUDE 0.75mm AT 2 h, FOR 3 DIRECTIONS.			① NO ELECTRICAL DISCONTINUITY OF 1 μs. ② NO DAMAGE, CRACK AND LOOSENESS, OF PARTS.			×	—		
SHOCK		490 m/s <sup>2</sup> DIRECTIONS OF PULSE 11 ms AT 3 TIME FOR 3 DIRECTION.			① NO ELECTRICAL DISCONTINUITY OF 1 μs. ② NO DAMAGE, CRACK AND LOOSENESS, OF PARTS.			×	—		
<b>ENVIRONMENTAL CHARACTERISTICS</b>											
RAPID CHANGE OF TEMPERATURE		TEMPERATURE -55→ 5 TO 35→85→ 5 TO 35 °C TIME 30→10 TO 15→30→10 TO 15min UNDER 5 CYCLES.			① CONTACT RESISTANCE: 30 mΩ MAX. ② INSULATION RESISTANCE:1000MΩ MIN. ③ NO DAMAGE, CRACK AND LOOSENESS, OF PARTS.			×	—		
DAMP HEAT (STEADY STATE)		EXPOSED AT 40±2 °C, 90 TO 95 %, 96 h.			① CONTACT RESISTANCE: 30 mΩ MAX. ② INSULATION RESISTANCE:500MΩ MIN. ③ NO DAMAGE, CRACK AND LOOSENESS, OF PARTS.			×	—		
RESISTANCE TO SOLDERING HEAT		1) AUTOMATIC SOLDERING (REFLOW) «REFLOW AREA» MAX 240°C WITHIN 10 sec. MIN 220°C 10 sec to 30 sec. «PREHEATING AREA» 150°C 100 sec. To 120 sec. PUT THROUGH IN REFLOW FUMACE TWICE. LEAVE IN AMBIENT TEMPERATURE AND HUMIDITY FOR 1 HOUR. CONNECTOR TEMPERATURE TO BE AMBIENT FOR SECOND REFLOW. 2) MANUAL SOLDERING SOLDERING IRON TEMPERATURE : 290±10°C, SOLDERING TIME : 3 sec. NO STRENGTH ON CONTACT.			NO DEFORMATION OF CASE OF EXCESSIVE LOOSENESS OF THE TERMINALS.			×			—
SOLDERABILITY		SOLDERING TEMPERATURE : 230°C SOLDERING TIME : 3 sec.			A NEW UNIFORM COATING OF SOLDER SHALL COVER MINIMUM OF 95 % OF THE SURFACE BEING IMMersed.			×	—		
REMARKS NOTE1:INCLUDE THE TEMPERATURE RISING BY CURRENT.					DRAWN	DESIGNED	CHECKED	APPROVED	RELEASED		
					M.Nakamoto	H.Umehara	T.Miyazaki	T.Oma			
					'04.03.25	'04.03.25	'04.03.25	04.03.25			
Unless otherwise specified, refer to JIS C 5402.											
Note QT: Qualification Test AT: Assurance Test ×:Applicable Test											
<b>HRS</b> HIROSE ELECTRIC CO., LTD.					SPECIFICATION SHEET						
CODE NO.(OLD)					PART NO.						
CL					DF3Z-*P-2V(20)						
DRAWING NO.			PART NO.					1	1		
ELC4-305939-10			CL543-								

TO

