

115-01300



Article Number: 115-01300

Description: Releasable Cable Tie, Release Tab, 20" Long, 250lb Tensile Strength, PA66HIRHSUV, Black, 25/pkg

Base Data	
Local Order Number	RT255R0HIRX2
Type	RT255R
Color	Black (BK)
Features and Benefits	<ul style="list-style-type: none"> • High impact, heat and UV stabilized releasable cable ties contain an impact modifier allowing greater flexibility and greater resistance to vibration. • Special design offers a release feature for quick and easy access to wire bundles. • Head design provides high tensile strength with very low insertion force even after repeated use.
Quantity Per	bag
Product Description	HellermannTyton releasable cable ties offer a release feature in the head allowing for easy access to wire bundles when changes are necessary. The head design guarantees high tensile strength even after repeated use, as well as a low insertion force . For high volume applications, tensioning tools are available to ensure consistent and safe installation.
Short Description	Releasable Cable Tie, Release Tab, 20" Long, 250lb Tensile Strength, PA66HIRHSUV, Black, 25/pkg
Product Dimensions	
Minimum Tensile Strength (Imperial)	250.0lbs
Minimum Tensile Strength (Metric)	1115.0N
Length L (Imperial)	20.0"
Length L (Metric)	508.0mm
Fixation Method	None
Identification Plate Position	none
Releasable Closure	Yes
Width W (Imperial)	0.5"
Width W (Metric)	12.6mm
Cable Tie Width Max. (Imperial)	0.49"
Cable Tie Width Max. (Metric)	12.5mm
Bundle Diameter Min. (Imperial)	0.49"
Bundle Diameter Min. (Metric)	12.5mm

115-01300



Product Dimensions	Bundle Diameter Max. (Imperial)	5.0"
	Bundle Diameter Max. (Metric)	127.0mm
Material and Specifications	Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
	Material Shortcut	PA66HIRHSUV
	Flammability	UL 94 HB
	Operating Temperature	-40°F to +230°F (-40°C to +110°C)
	ROHS Compliant	Yes
	Certification/Specification	UL
	UL Recognized (US and Canada)	Yes
	Logistic and Packaging	
	Package Quantity (Imperial)	25
	Package Quantity (Metric)	25
	Customs Number(Schedule B)	3926909987