
## **BELT-TY™ In-Line Cable Ties Nylon 6.6**

- Head designed for no protrusion of cut-off tie
- Low profile head (35% lower than conventional 90° entry cable ties)
- Fully rounded edges on head and strap
- · Rounded tip and aggressive grip
- Finger grip shaped head
- Curved tip

- Protects adjacent cables and protects workers arms and hands
- Avoids snags and reduces overall bundle size
- No sharp edges in contact with cable insulation
- Easy to grip for assembly
- Positive grip when threading tie
- Material: Nylon 6.6







- Parallel-entry cable ties that thread like a belt (at 180°) with the same performance of conventional (90° entry) cable ties
- The BELT-TY™ In-Line Cable Tie design reduces the long cut-off danger of an incorrectly applied conventional cable tie



				Head	Head	Max.	Min. Loop	Recommended	Packaging*			
Part Number	Length A	Width B	Thickness C	Height D	Width E in. (mm)	Bundle Dia.	Tensile Strength	PANDUIT® Installation Tool Part No.	Std. Pkg.	Std. Ctn.	Bulk Pkg.	Bulk Ctn.
	in. (mm)	in. (mm)	in. (mm)	in. (mm)	in. (mm)	in. (mm)	Lbs. (N)	1001 Part No.	Qty.	Qty.	Qty.	Qty.
MINIATURE CROSS SECTION												
ILT1M-M‡	4.8 (122)	.098 (2.5)	.044 (1.1)	.110 (2.8)	.190 (4.8)	1.10 (28)	18 (80)	GTS, GS2B, PTS or PPTS	_	_	1000	50,000
INTERMEDIATE CROSS SECTION												
ILT1.5I-M‡	5.4 (137)	.142 (3.6)	.052 (1.3)	.130 (3.3)	.260 (6.6)	1.38 (35)	30 (133)	GTS, GS2B, PTS or PPTS	_	_	1000	25,000
STANDARD CROSS SECTION												•
ILT2S-M‡	8.3 (211)	.190 (4.8)	.052 (1.3)	.140 (3.6)	.316 (8.0)	1.88 (48)		GTS, GS2B, GTH, GS4H, PTS or PPTS	_	_	1000	10,000
ILT3S-M‡	11.5 (292)					3.00 (76)	50 (222)		_	_	1000	5000
ILT4S-M‡	14.7 (373)					4.00 (102)			_	_	1000	5000
LIGHT-HEAVY CROSS SECTION												
ILT4LH-TL‡	14.8 (376)	.300 (7.6)	.075 (1.9)	.250 (6.4)	.475 (12.1)	4.00 (102)	120 (534)	GTH, GS4H or PPTEH	_	_	250	2500
ILT6LH-C‡	21.2 (538)					6.00 (152)			_	_	100	500