APPLICA	BLE STAN	DARD				_			
	OPERATING TEMPERATURE RANGE		-35°C TO +85°C(NOT	E 1)	STORAGE TEMPERATURE RANGE		-10°C TO +60°C		
RATING VOLTAGE			30V AC		APPLICABLE CONNECTOR		DF40*-30DS-0.4V		
	CURRENT		0. 3A						
			SPECII	FICAT	IONS				
	ГЕМ		TEST METHOD			REQU	JIREMENTS	QT	АТ
	RUCTION	T			1,,,,,				
GENERAL EX	AMINATION	VISUALLY AND BY MEASURING INSTRUMENT. CONFIRMED VISUALLY.			ACCO	RDING TO DE	RAWING.	X	X
ELECTRIC CHARA								X	X
		20mV AC OR LESS 1khz,1m A .			180mΩ	MAX.		X	
INSULATIO	N.	100V DC.			50MO I	50MΩ MIN.			_
RESISTANCE					30101521				_
VOLTAGE PROOF		100V AC FOR 1 min.			NO FL	NO FLASHOVER OR BREAKDOWN.			_
MECHAI	NICAL CHA	RACTI	ERISTICS						
MECHANICAL OPERATION		3000TIMES INSERTIONS AND EXTRACTIONS.			2 NO	① CONTACT RESISTANCE: 180mΩ MAX. ② NO DAMAGE, CRACK OR LOOSENESS OF PARTS.			_
COUN	IT D	SCRIPTI	ON OF REVISIONS	D	ESIGNED		CHECKED	DA	TE
Δ							1		
REMARKS NOTE1: INCLUDE THE TEMPERAT			ATURE RISING BY CURRENT			APPROVED	1	11.0	
						CHECKED DESIGNED	AR. TAKAHASHI TR. YUNOKI	11. 07. 29 11. 07. 29	
Unless otherwise specified, refer			er to JIS C 5402.			DRAWN	TR. YUNOKI	11. 07. 29	
Note QT:Q	ualification Tes	t AT:Ass	urance Test X:Applicable Test	:	DRAWING NO.		ELC4-31564		
RS SPECIFICATION SHEET				Р	PART NO. DF40JC-30DP-0. 4V (5		3)		
HIRO		OSE ELECTRIC CO., LTD.			ODE NO.	CL684-4070-0-53		A	1/1