



EPCOS Product Brief 2016

Film Capacitors

PCC Power Capacitors for HybridPACK™ IGBT Modules



Technology




Fig. 1: Cross section of a metalized film capacitor


Fig. 2: Self-healing property of a metalized film capacitor

Metallized film capacitors (fig.1) have the advantage that for certain failures in the dielectric the capacitor will not go into short thanks to the ultrathin metallized electrode (thickness typical 10 to 100 nm) and the use of aluminium as material for the electrodes. If a breakdown occurs, the aluminium will evaporate around the breakdown spot and immediately oxidize to Al_2O_3 , which is an excellent insulator. So the breakdown spot becomes high-impedance and is insulated from the rest of the capacitor. The insulated area is formed in a few microseconds and ensures the full functionality of the capacitor after breakdown.

This behaviour is called “clearing” or “self-healing” (fig. 2). In principle there should not be any further clearing during the service life, since all capacitors are typically “cleared” with a voltage of 1.5 times the rated voltage during the production process.

Additionally, to limit the energy dissipation during a clearing event, for some designs at least one electrode is divided into segments, connected by small links or fuses. The capacitors are typically

named “segmented” or “structured” metalized film capacitors. See fig. 3 example of a “T-segmentation”:



EPCOS possesses different winding technologies:

- The stacked technology, typically used for PCC film capacitors, for which the film is already wound flat on the winding machine. This technology offers the highest fill factor and the lowest ESR.
- The flat pressed winding technology which is most commonly used on the market for this type of application today. This technology offers the lowest costs at a good performance.

Typical rated voltages (V):

IGBT rated voltage	PCC capacitor	
	Rated voltage	Maximum voltage ¹⁾
650 - 705	450	500
750	500	550
1200	900	950

1) For limited time, please refer to data sheet


The rated voltage is defined as the continuous operating voltage taking into account for the calculation of the expected lifetime.

The maximum voltage is the maximum operating voltage to be applied on the capacitor for short operations (e.g. up to 10% of the expected calculated lifetime).

A detailed lifetime calculation based on a mission profile (voltage, temperature) can be submitted upon request.

PCC for Infineon HybridPack™ 1 (HP1)

PRELIMINARY



HP1 platform 650 V – FS***xR07A1**



Ordering code	C _R	V _{RDC}	I _{max} ¹⁾	L _{self}	R _S	\hat{I}	I _S	tan δ	Dimensions L x W x H mm	Weight kg	Fig.
	μ F	V	A	nH	m Ω	kA	kA	120 Hz			
B25655J4307K001	300	450	120	30	0.8	0.9	2.7	$8 \cdot 10^{-4}$	140 x 72 x 50	0.8	1a
B25655P4467K000	460	450	150	25	0.6	1.5	5.0	$5 \cdot 10^{-4}$	140 x 72 x 50	0.8	1a
B25655P4567K000	560	450	150	25	0.6	1.8	5.6	$5 \cdot 10^{-4}$	140 x 72 x 50	0.8	1a
B25655P4407K100 ²⁾	400	450	120	25	0.8	1.4	4.4	$5 \cdot 10^{-4}$	140 x 72 x 50	0.8	1a
B25655P4507K100 ²⁾	500	450	120	25	0.8	1.6	5.0	$5 \cdot 10^{-4}$	140 x 72 x 50	0.8	1a
B25655P4607K100 ³⁾	600	450	120	25	0.8	2.0	6.0	$5 \cdot 10^{-4}$	140 x 72 x 50	0.8	1a
B25655P4467K001	460	450	150	25	0.6	1.5	5.0	$5 \cdot 10^{-4}$	140 x 72 x 50	0.8	1b
B25655P4567K001	560	450	150	25	0.6	1.8	5.6	$5 \cdot 10^{-4}$	140 x 72 x 50	0.8	1b
B25655P4407K101 ²⁾	400	450	120	25	0.8	1.4	4.4	$5 \cdot 10^{-4}$	140 x 72 x 50	0.8	1b
B25655P4507K101 ²⁾	500	450	120	25	0.8	1.6	5.0	$5 \cdot 10^{-4}$	140 x 72 x 50	0.8	1b
B25655P4607K101 ³⁾	600	450	120	25	0.8	2.0	6.0	$5 \cdot 10^{-4}$	140 x 72 x 50	0.8	1b

HP1-DC6 platform 705 V – FS***R07A3**

Ordering code	C _R	V _{RDC}	I _{max} ¹⁾	L _{self}	R _S	\hat{I}	I _S	tan δ	Dimensions L x W x H mm	Weight kg	Fig.
	μ F	V	A	nH	m Ω	kA	kA	120 Hz			
B25655P4607J011	600	450	150	25	0.6	1.5	4.5	$10 \cdot 10^{-4}$	140 x 72 x 50	0.9	2a
B25655P4607J021 ²⁾	600	450	150	25	0.6	1.5	4.5	$10 \cdot 10^{-4}$	140 x 72 x 50	0.75	2b
B25655P4477J111	470	450	120	25	0.8	1.1	3.0	$10 \cdot 10^{-4}$	140 x 72 x 50	0.9	2a
B25655P4477J121 ²⁾	470	450	120	25	0.8	1.1	3.0	$10 \cdot 10^{-4}$	140 x 72 x 50	0.75	2b

- 1) Considering maximum hot spot temperature at +105 °C and cooling efficiency to be validated.
- 2) Preferred types.
- 3) Reduced life time, please refer to data sheet.

Green marked lines: New types .../K/J1xx available during 2016.

Red marked line: Not recommended for new designs.

Further mechanical configurations and capacitor values upon request.
2-line EMC filter for HP1-DC6 platform available under preliminary order code P100316-P001.

More information for Infineon HP1-DC6 module, refer to: <http://www.infineon.com/>

PCC for Infineon HybridPack™ 2 (HP2)

PRELIMINARY




Fig. 3a – For HP2 platform

Fig. 3b – For HP2 platform

Additional fixing may be necessary upon application requirements (see page 5 with side mounting terminals)

HP2 platform 680 V – FS***R07A2**



Ordering code	C _R μF	V _{RDC} V	I _{max} ¹⁾ A	L _{self} nH	R _S mΩ	\hat{I} kA	I _S kA	tanδ 120 Hz	Dimensions L x W x H mm	Weight kg	Fig.
B25655J4507K005	500	450	120	15	1.0	1.5	4.5	5 · 10 ⁻⁴	237 x 72 x 50	1.2	3a
B25655P4707K030	700	450	190	15	0.5	2.5	7.5	5 · 10 ⁻⁴	237 x 72 x 50	1.2	3a
B25655P4907K030	900	450	190	15	0.5	3.0	9.0	5 · 10 ⁻⁴	237 x 72 x 50	1.2	3a
B25655P4108K030	1000	450	190	15	0.5	3.2	10.0	5 · 10 ⁻⁴	237 x 72 x 50	1.2	3a
B25655P4507K130 ²⁾	500	450	170	15	0.7	1.8	5.5	5 · 10 ⁻⁴	237 x 72 x 50	1.2	3a
B25655P4507K140 ²⁾	500	450	170	15	0.7	1.8	5.5	5 · 10 ⁻⁴	237 x 72 x 50	1.2	3b
B25655P4707K130 ²⁾	700	450	170	15	0.7	2.8	8.4	5 · 10 ⁻⁴	237 x 72 x 50	1.2	3a
B25655P4707K140 ²⁾	700	450	170	15	0.7	2.8	8.4	5 · 10 ⁻⁴	237 x 72 x 50	1.2	3b
B25655P4857K130	850	450	170	15	0.7	3.1	9.3	5 · 10 ⁻⁴	237 x 72 x 50	1.2	3a
B25655P4857K140	850	450	170	15	0.7	3.1	9.3	5 · 10 ⁻⁴	237 x 72 x 50	1.2	3b
B25655P4907K130 ²⁾	900	450	170	15	0.7	3.3	9.9	5 · 10 ⁻⁴	237 x 72 x 50	1.2	3a
B25655P4907K140 ²⁾	900	450	170	15	0.7	3.3	9.9	5 · 10 ⁻⁴	237 x 72 x 50	1.2	3b
B25655P4108K130 ³⁾	1000	450	170	15	0.7	3.3	10.0	5 · 10 ⁻⁴	237 x 72 x 50	1.2	3a
B25655P4108K140 ³⁾	1000	450	170	15	0.7	3.3	10.0	5 · 10 ⁻⁴	237 x 72 x 50	1.2	3b

1) Considering maximum hot spot temperature at +105 °C and cooling efficiency to be validated.

2) Preferred types.


3) Reduced life time, please refer to data sheet.

Green marked lines: New types .../K/J1xx available during 2016.

Red marked line: Not recommended for new designs.

PCC for Infineon HybridPack™ 2 (HP2)

PRELIMINARY



HP2 platform 680 V – FS***R07A2**



Ordering code	C _R μF	V _{RDC} V	I _{max} ¹⁾ A	L _{self} nH	R _S mΩ	\hat{I} kA	I _S kA	tanδ 120 Hz	Dimensions L x W x H mm	Weight kg	Fig.
B25655P4707K031	700	450	190	15	0.5	2.5	7.5	5 · 10 ⁻⁴	237 x 72 x 50	1.2	4a
B25655P4907K031	900	450	190	15	0.5	3.0	9.0	5 · 10 ⁻⁴	237 x 72 x 50	1.2	4a
B25655P4108K031	1000	450	190	15	0.5	3.2	10.0	5 · 10 ⁻⁴	237 x 72 x 50	1.2	4a
B25655P4507K131 ²⁾	500	450	170	15	0.7	1.8	5.5	5 · 10 ⁻⁴	237 x 72 x 50	1.2	4a
B25655P4507K141 ²⁾	500	450	170	15	0.7	1.8	5.5	5 · 10 ⁻⁴	237 x 72 x 50	1.2	4b
B25655P4707K131 ²⁾	700	450	170	15	0.7	2.8	8.4	5 · 10 ⁻⁴	237 x 72 x 50	1.2	4a
B25655P4707K141 ²⁾	700	450	170	15	0.7	2.8	8.4	5 · 10 ⁻⁴	237 x 72 x 50	1.2	4b
B25655P4857K131	850	450	170	15	0.7	3.1	9.3	5 · 10 ⁻⁴	237 x 72 x 50	1.2	4a
B25655P4857K141	850	450	170	15	0.7	3.1	9.3	5 · 10 ⁻⁴	237 x 72 x 50	1.2	4b
B25655P4907K131 ²⁾	900	450	170	15	0.7	3.3	9.9	5 · 10 ⁻⁴	237 x 72 x 50	1.2	4a
B25655P4907K141 ²⁾	900	450	170	15	0.7	3.3	9.9	5 · 10 ⁻⁴	237 x 72 x 50	1.2	4b
B25655P4108K131 ³⁾	1000	450	170	15	0.7	3.3	10.0	5 · 10 ⁻⁴	237 x 72 x 50	1.2	4a
B25655P4108K141 ³⁾	1000	450	170	15	0.7	3.3	10.0	5 · 10 ⁻⁴	237 x 72 x 50	1.2	4b

1) Considering maximum hot spot temperature at +105 °C and cooling efficiency to be validated.

2) Preferred types.

3) Reduced life time, please refer to data sheet.

Green marked lines: New types ...K/J1xx available during 2016.

PCC for Infineon HybridPack™ Drive (HP Drive)

PRELIMINARY



Fig. 5 – For HP Drive platform
With side mounting terminals

HP Drive platform 750 V – FS***R08A6**



Ordering code	C _R μF	V _{RDC} V	I _{max} ¹⁾ A	L _{self} nH	R _S mΩ	\hat{I} kA	I _S kA	tanδ 120 Hz	Dimensions L x W x H mm	Weight kg	Fig.
B25655P5507K051	500	500	160	15	0.5	2.0	6.0	5 · 10 ⁻⁴	154 x 72 x 50	0.8	5
B25655P5407K151 ²⁾	400	500	150	15	0.6	2.0	6.0	5 · 10 ⁻⁴	154 x 72 x 50	0.8	5

HP Drive platform 1200 V – FS***R12A6**

Ordering code	C _R μF	V _{RDC} V	I _{max} ¹⁾ A	L _{self} nH	R _S mΩ	\hat{I} kA	I _S kA	tanδ 120 Hz	Dimensions L x W x H mm	Weight kg	Fig.
B25655P9127K151 ²⁾	120	900	120	15	0.8	3.5	11.0	5 · 10 ⁻⁴	154 x 72 x 50	0.8	5

1) Considering maximum hot spot temperature at +105 °C and cooling efficiency to be validated.

2) Preferred types.

Green marked lines: New types .../K/J1xx available during 2016.

Cautions and Warnings

PRELIMINARY



Specifications and characteristics	
Capacitance tolerance	K \pm 10% / J \pm 5%
$\tan \delta_0$	$2 \cdot 10^{-4}$
V_R	450 / 500 / 900 V DC
V_s	600 / 700 / 1300 V DC

Test data	
Voltage between terminals V_{TT}	675 / 750 / 1350 V DC, 10 s
Voltage between terminals and case V_{TC}	3000 V DC, 10 s
$R_{ins} C$	≥ 10000 s
Life expectancy	Up to 15 000 hours @ THS ¹⁾
αFQ	300 fit
Values after Test Ca, IEC 68-2 (21 days, 40 °C, 93% rel. humidity)	
$ \Delta C/C $	$\leq 5\%$
$\Delta \tan \delta$	$\leq 5 \cdot 10^{-4}$
$R_{ins} C$	≤ 3000 s
Tested based on AEC Q-200 rev. D	

Climatic category	40/105/21
T_{stg}	-45 ... +110 °C
T_{min}	-40 °C
T_{max}	+105 °C
THS (maximum hot spot temperature)	+105 °C
Max. permissible humidity	95%

Construction and general data	
Resin filling	Polyurethane resin
Case	Plastic (Polycarbonate)
Terminals	Flat copper (tinned)
Creepage and clearance distance	Figure 1: 9 mm Figure 2: 8 mm
Cooling	to be confirmed
Degree of protection	Indoor mounting (IP54)
RoHS compliant	

1) To be confirmed; depending on the application

Display of ordering codes for EPCOS products

The ordering code for one and the same product can be represented differently in data sheets, data books, other publications and the website of EPCOS, or in order-related documents such as shipping notes, order confirmations and product labels. The varying representations of the ordering codes are due to different processes employed and do not affect the specifications of the respective products. Detailed information can be found on the Internet under www.epcos.com/orderingcodes

HybridPack is a trademark of Infineon Technologies AG

Important information Some parts of this publication contain statements about the suitability of our products for certain areas of application. These statements are based on our knowledge of typical requirements that are often placed on our products. We expressly point out that these statements cannot be regarded as binding statements about the suitability of our products for a particular customer application. It is incumbent on the customer to check and decide whether a product is suitable for use in a particular application. This publication is only a brief product survey which may be changed from time to time. Our products are described in detail in our data sheets. The Important notes (www.epcos.com/ImportantNotes) and the product-specific Cautions and warnings must be observed. All relevant information is available through our sales offices.