

THIS INFORMATION IS CONFIDENTIAL AND PROPRIETARY TO TYCO
AND ITS SUBSIDIARIES. IT MAY NOT BE REPRODUCED, COPIED,
OR DISCLOSED TO ANYONE EXCEPT AUTHORIZED STAFF
MEMBERS OR CONTRACTORS WITHOUT WRITTEN AUTHORIZATION.
TYCO ELECTRONICS CORPORATION, HARRISBURG, PENNSYLVANIA

DRG NO

1

THIS DRAWING IS A CONTROLLED DOCUMENT.

Restricted to: General Release

USED ON

Part #	L (meters)	L (feet)	MT-RJ (No Pins), Black	LC-Duplex Secure, Blue		
			IL (dB)	RL (dB)	IL (dB)	RL (dB)
0-1907125-1	0.950 - 1.050	3.11 - 3.44	0.5	20	0.5	-
0-1907125-2	1.950 - 2.050	6.39 - 6.72	0.5	20	0.5	-
0-1907125-3	2.950 - 3.050	9.67 - 10.00	0.5	20	0.5	-
0-1907125-4	3.920 - 4.080	12.86 - 13.38	0.51	20	0.51	-
0-1907125-5	4.920 - 5.080	16.14 - 16.66	0.51	20	0.51	-
0-1907125-6	5.920 - 6.080	19.42 - 19.94	0.51	20	0.51	-
0-1907125-7	6.920 - 7.080	22.70 - 23.22	0.51	20	0.51	-
0-1907125-8	7.920 - 8.080	25.98 - 26.50	0.51	20	0.51	-
0-1907125-9	8.850 - 9.150	29.03 - 30.01	0.51	20	0.51	-
1-1907125-0	9.850 - 10.150	32.31 - 33.30	0.52	20	0.52	-
1-1907125-1	10.850 - 11.150	35.59 - 36.58	0.52	20	0.52	-
1-1907125-2	11.850 - 12.150	38.87 - 39.86	0.52	20	0.52	-
1-1907125-3	12.850 - 13.150	42.15 - 43.14	0.52	20	0.52	-
1-1907125-4	13.850 - 14.150	45.43 - 46.42	0.52	20	0.52	-
1-1907125-5	14.850 - 15.150	48.72 - 49.70	0.52	20	0.52	-
1-1907125-6	15.840 - 16.160	51.96 - 53.01	0.52	20	0.52	-
1-1907125-7	16.830 - 17.170	55.21 - 56.33	0.53	20	0.53	-
1-1907125-8	17.820 - 18.180	58.46 - 59.64	0.53	20	0.53	-
1-1907125-9	18.810 - 19.190	61.71 - 62.95	0.53	20	0.53	-
2-1907125-0	19.800 - 20.200	64.96 - 66.27	0.53	20	0.53	-
2-1907125-1	20.790 - 21.210	68.20 - 69.58	0.53	20	0.53	-
2-1907125-2	21.780 - 22.220	71.45 - 72.90	0.53	20	0.53	-
2-1907125-3	22.770 - 23.230	74.70 - 76.21	0.53	20	0.53	-
2-1907125-4	23.760 - 24.240	77.95 - 79.52	0.54	20	0.54	-
2-1907125-5	24.750 - 25.250	81.20 - 82.84	0.54	20	0.54	-
2-1907125-6	25.740 - 26.260	84.44 - 86.15	0.54	20	0.54	-
2-1907125-7	26.730 - 27.270	87.69 - 89.46	0.54	20	0.54	-
2-1907125-8	27.720 - 28.280	90.94 - 92.78	0.54	20	0.54	-
2-1907125-9	28.710 - 29.290	94.19 - 96.09	0.54	20	0.54	-
3-1907125-0	29.700 - 30.300	97.44 - 99.40	0.55	20	0.55	-
3-1907125-1	30.690 - 31.310	100.68 - 102.72	0.55	20	0.55	-
3-1907125-2	31.680 - 32.320	103.93 - 106.03	0.55	20	0.55	-
3-1907125-3	32.670 - 33.330	107.18 - 109.35	0.55	20	0.55	-
3-1907125-4	33.660 - 34.340	110.43 - 112.66	0.55	20	0.55	-
3-1907125-5	34.650 - 35.350	113.68 - 115.97	0.55	20	0.55	-
3-1907125-6	35.640 - 36.360	116.92 - 119.29	0.55	20	0.55	-
3-1907125-7	36.630 - 37.370	120.17 - 122.60	0.56	20	0.56	-
3-1907125-8	37.620 - 38.380	123.42 - 125.91	0.56	20	0.56	-
3-1907125-9	38.610 - 39.390	126.67 - 129.23	0.56	20	0.56	-
4-1907125-0	39.600 - 40.400	129.92 - 132.54	0.56	20	0.56	-
4-1907125-1	40.590 - 41.410	133.16 - 135.85	0.56	20	0.56	-
4-1907125-2	41.580 - 42.420	136.41 - 139.17	0.56	20	0.56	-

Qty	U of M	Description	Item No.
1	piece	LC Duplexclip, black	14
1	piece	MT-RJ, SPRING PUSH, UNIVERSAL	13
1	piece	PIN KEEPER, 3.8MM	12
AR	meter	2 fiber, 62.5/125, 1.8 mm, Twinzip, Orange, OFNR (Riser)	11
2	piece	Trace Label	10
1	piece	CRIMP EYELET, MT-RJ	9
1	piece	HOUSING, CONN, MT-RJ,BLACK	8
1	piece	SPRING, MT-RJ, 3.8 DESIGN	7
2	piece	LC, SC, FC Straight Boot, Beige	6
2	piece	Eyelet/Shrink tube assembly - White	5
1	piece	DUST COVER, MT-RJ	4
1	piece	MT-RJ FERRULE, THERMOPLAST,MM	3
1	piece	MT-RJ TwinZip Bend Limiting Boot, Beige	2
2	piece	LC Connector Assy, 1.6mm-2.0mm, MM	1

LOC	CE	DIST	16												
CAB Customer Layout Rev.D															
8	7	6	5												
4	3	2	1												
<table border="1"> <tr> <td>A</td> <td>Rev Per EC#</td> <td>RELEASE</td> <td>2/15/2006</td> <td>-</td> <td>DF</td> </tr> <tr> <td>P</td> <td>LTR</td> <td>REVISION RECORD</td> <td>DATE</td> <td>DIN</td> <td>APVD</td> </tr> </table>				A	Rev Per EC#	RELEASE	2/15/2006	-	DF	P	LTR	REVISION RECORD	DATE	DIN	APVD
A	Rev Per EC#	RELEASE	2/15/2006	-	DF										
P	LTR	REVISION RECORD	DATE	DIN	APVD										
Customer Print				SCALE NTS	SIZE A2	DRAWING NO C-1907125	SHEET 2 of 4	REV A							

Part #		L (meters)	L (feet)	MT-RJ (No Pins), Black		LC-Duplex Secure, Blue	
Part #				IL (dB)	RL (dB)	IL (dB)	RL (dB)
4-1907125-3		42.570 - 43.430	139.66 - 142.48	0.56	20	0.56	-
4-1907125-4		43.560 - 44.440	142.91 - 145.80	0.57	20	0.57	-
4-1907125-5		44.550 - 45.450	146.16 - 149.11	0.57	20	0.57	-
4-1907125-6		45.540 - 46.460	149.40 - 152.42	0.57	20	0.57	-
4-1907125-7		46.530 - 47.470	152.65 - 155.74	0.57	20	0.57	-
4-1907125-8		47.520 - 48.480	155.90 - 159.05	0.57	20	0.57	-
4-1907125-9		48.510 - 49.490	159.15 - 162.36	0.57	20	0.57	-
5-1907125-0		49.500 - 50.500	162.40 - 165.68	0.58	20	0.58	-
5-1907125-1		50.490 - 51.510	165.64 - 168.99	0.58	20	0.58	-
5-1907125-2		51.480 - 52.520	168.89 - 172.30	0.58	20	0.58	-
5-1907125-3		52.470 - 53.530	172.14 - 175.62	0.58	20	0.58	-
5-1907125-4		53.460 - 54.540	175.39 - 178.93	0.58	20	0.58	-
5-1907125-5		54.450 - 55.550	178.64 - 182.25	0.58	20	0.58	-
5-1907125-6		55.440 - 56.560	181.88 - 185.56	0.58	20	0.58	-
5-1907125-7		56.430 - 57.570	185.13 - 188.87	0.59	20	0.59	-
5-1907125-8		57.420 - 58.580	188.38 - 192.19	0.59	20	0.59	-
5-1907125-9		58.410 - 59.590	191.63 - 195.50	0.59	20	0.59	-
6-1907125-0		59.400 - 60.600	194.88 - 198.81	0.59	20	0.59	-
6-1907125-1		60.390 - 61.610	198.12 - 202.13	0.59	20	0.59	-
6-1907125-2		61.380 - 62.620	201.37 - 205.44	0.59	20	0.59	-
6-1907125-3		62.370 - 63.630	204.62 - 208.75	0.59	20	0.59	-
6-1907125-4		63.360 - 64.640	207.87 - 212.07	0.6	20	0.6	-
6-1907125-5		64.350 - 65.650	211.12 - 215.38	0.6	20	0.6	-
6-1907125-6		65.340 - 66.660	214.37 - 218.70	0.6	20	0.6	-
6-1907125-7		66.330 - 67.670	217.61 - 222.01	0.6	20	0.6	-
6-1907125-8		67.320 - 68.680	220.86 - 225.32	0.6	20	0.6	-
6-1907125-9		68.310 - 69.690	224.11 - 228.64	0.6	20	0.6	-
7-1907125-0		69.300 - 70.700	227.36 - 231.95	0.61	20	0.61	-
7-1907125-1		70.290 - 71.710	230.61 - 235.26	0.61	20	0.61	-
7-1907125-2		71.280 - 72.720	233.85 - 238.58	0.61	20	0.61	-
7-1907125-3		72.270 - 73.730	237.10 - 241.89	0.61	20	0.61	-
7-1907125-4		73.260 - 74.740	240.35 - 245.20	0.61	20	0.61	-
7-1907125-5		74.250 - 75.750	243.60 - 248.52	0.61	20	0.61	-
7-1907125-6		75.240 - 76.760	246.85 - 251.83	0.61	20	0.61	-
7-1907125-7		76.230 - 77.770	250.09 - 255.15	0.62	20	0.62	-
7-1907125-8		77.220 - 78.780	253.34 - 258.46	0.62	20	0.62	-
7-1907125-9		78.210 - 79.790	256.59 - 261.77	0.62	20	0.62	-
8-1907125-0		79.200 - 80.800	259.84 - 265.09	0.62	20	0.62	-

THIS INFORMATION IS CONFIDENTIAL AND PROPRIETARY TO TYCO ELECTRONICS CORPORATION AND ITS WORLDWIDE SUBSIDIARIES AND AFFILIATES. IT MAY NOT BE DISCLOSED TO ANYONE, OTHER THAN TYCO ELECTRONICS PERSONNEL, WITHOUT WRITTEN AUTHORIZATION FROM TYCO ELECTRONICS CORPORATION, HARRISBURG, PENNSYLVANIA.

THIS INFORMATION
ELECTRONICS CORP
AFFILIATES, IT WA
TYCO ELECTRONICS
FROM TYCO ELECTR
CE
DIST
OSA
16

CAC Customer Layout Rev. D

8

7

1

Restricted to: General Release

Label 1

Per specification 107-1645-1



- Trace # - Bar Code
- Trace # - Human Readable
- Part Number
- Country of Origin

This label is used on all lengths on this drawing.

Label 2

Per specification 107-1645-1



- Trace # - Bar Code
- Trace # - Human Readable
- Part Number
- Country of Origin

This label is used on all lengths on this drawing.

DNG NO

THIS DRAWING IS A CONTROLLED DOCUMENT.

THIS INFORMATION IS CONFIDENTIAL AND PROPRIETARY TO TYCO ELECTRONICS CORPORATION AND ITS WORLDWIDE SUBSIDIARIES AND AFFILIATES. IT MAY NOT BE DISCLOSED TO ANYONE, OTHER THAN TYCO ELECTRONICS PERSONNEL, WITHOUT WRITTEN AUTHORIZATION FROM TYCO ELECTRONICS CORPORATION, HARRISBURG, PENNSYLVANIA.

THIS INFORMATION IS ELECTRONICS CORP. AFFILIATES. IT MAY TYCO ELECTRONICS FROM TYCO ELECTR	LOC CE DIST 16 DST.
--	---------------------------------

CAC Customer Layout Rev. D

1

三

1

1

1

1

1

1