DIN 41612 · complementary type M invers



Dimensions in mm

Number of contacts

78+2, 60+4, 42+6, 24+8, 6+10

Female connectors

Identification	No. of Contact contacts arrangement	Part number Performance	ce levels according to IEC 6	60 603-2. Explanation chapter 00
Female connector with angled solder pins (without special contacts)*	78 + 2 \$\begin{align*} \begin{align*} 2 \cdot 6 \cdot 8 \cdot 9 \cdot 9 \cdot	Performance level 3 on request	09 73 278 6801 09 73 260 6801 09 73 242 6801 09 73 224 6801 09 73 206 6801	Performance level 1 on request
Dimensions	C-C (2:1) 10,5=0.1 10,5=			
Order high current, high voltage, coaxial and fibre optic contacts separately	2 5 8 11 14 16 19 22 25 28 31— position			
Board drillings Mounting side Board drillings depend on type and special contact	10x (2) (2) (2) (2) (2) (3) (4) (4) (4) (4) (4) (4) (4) (4) (4) (4	5,08 5,08 7,62 4x 7,62 (=30,48) 73,66	row all holes Ø0,05	Type c 78 + 2 25 x 2.54 = 63.5 60 + 4 19 x 2.54 = 48.26 42 + 6 13 x 2.54 = 33.02 24 + 8 7 x 2.54 = 17.78 6 + 10 1 x 2.54 = 2.54
	Female connector with angled solder pins (without special contacts)* Dimensions Order high current, high voltage, coaxial and fibre optic contacts separately Board drillings Mounting side	Identification contacts arrangement Female connector with angled solder pins (without special contacts)* 78 + 2 1000000000000000000000000000000000000	Female connector with angled solder pins (without special contacts)* Temple connector with angled solder pins (without special contacts)* Temple connector with angled solder pins (without special contacts)* Temple connector with angled solder pins (without special contacts)* Temple connector with angled solder pins (without special contacts)* Temple connector with angled solder pins (without special contacts)* Temple connector with angled solder pins (without special contacts)* Temple connector with angled solder pins (without special contacts)* Temple connector with angled solder pins (without special contacts)* Temple connector with angled solder pins (without special contacts)* Temple connector with angled solder pins (without special contacts)* Temple connector with angled solder pins (without special contacts)* Temple connector without special contacts)* Temple connector without special contacts (without special contacts)* Temple connector without special contacts (without special contacts)* Temple contacts (without special cont	Content Cont

loading

= 0,1 A −

^{*} Pre-loaded with special contacts on request