

VGA with RS232 over Cat5/Cat6 Extender Kit, Box-Style Transmitter and Receiver, 1920x1440 at 60Hz (discontinued)

MODEL NUMBER: **B130-101S**



Description

Tripp Lite's B130-101S allows you to extend a 1920 x 1440 (60Hz) Video and RS232 Serial signal up to 500 ft., or a 1024 x 768 (60Hz) Video and RS232 Serial signal up to 1,000 ft., when using 24Awg, Solid Wire Cat5e/6 cable, such as Tripp Lite's [N022-01K-GY](#) (Cat5) and [N222-01K-GY](#) (Cat6). For optimal image quality between 500 and 1,000 ft., use Zero-Skew cable, such as Tripp Lite [P524-01K](#). The local (Transmitter) unit features an additional VGA port for the connection of a local monitor. The remote (Receiver) unit features built-in Equalization and Gain controls to adjust the video image. Includes mounting hardware for both local and remote units, allowing them to be wallmounted, rackmounted or pole mounted. Ideal for digital signage situations needing serial access, such as bar code scanners or touchscreen monitors.

Features

- Extends a 1920 x 1440 (60Hz) Video and RS232 Serial signal up to 500 ft., or a 1024 x 768 (60Hz) Video and RS232 Serial signal up to 1,000 ft., when using 24Awg, Solid Wire Cat5e/6 cable, such as Tripp Lite's [N022-01K-GY](#)(Cat5) and [N222-01K-GY](#) (Cat6)
- For optimal image quality between 500 and 1,000 ft., use Zero-Skew cable, such as Tripp Lite [P524-01K](#)
- Supports bi-directional communication
- The local (Transmitter) unit features an additional VGA port for the connection of a local monitor
- The remote (Receiver) unit features built-in Equalization and Gain controls to adjust the video image
- Includes mounting hardware for both the local and remote units, allowing them to be wallmounted, rackmounted or pole mounted
- Ideal for digital signage situations needing serial access, such as bar code scanners or touchscreen monitors
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule Purchases

Specifications

Highlights

- Extends a 1920 x 1440 (60Hz) Video and RS232 Serial signal up to 500 ft., or a 1024 x 768 (60Hz) Video and RS232 Serial signal up to 1,000 ft., when using 24Awg, Solid Wire Cat5e/6 cable, such as Tripp Lite's [N022-01K-GY](#)(Cat5) and [N222-01K-GY](#) (Cat6)
- For optimal image quality between 500 and 1,000 ft., use Zero-Skew cable, such as Tripp Lite [P524-01K](#)
- Supports bi-directional communication
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule Purchases

Package Includes

- Local (Transmitter) unit
- Remote (Receiver) unit
- Mini-Screwdriver for EQ/Gain adjustment
- (x2) Mounting Hardware kits
- (x2) External Power Supply (Input: 100-240V, 50/60Hz, 0.5A Output: 5V, 2A)
- 3.5mm Male to DB9 Male adapter cable
- 3.5mm Male to DB9 female adapter cable
- Owner's Manual



PHYSICAL	
Shipping Weight (lbs.)	2.0
Shipping Weight (kg)	0.91
CONNECTIONS	
Ports	1
Side A - Connector 1	(2) HD15 (FEMALE)
Side A - Connector 2	RJ45 (FEMALE)
Side A - Connector 3	DB9 (MALE)
Side B - Connector 1	HD15 (FEMALE)
Side B - Connector 2	DB9 (FEMALE)
Side B - Connector 3	RJ45 (FEMALE)
WARRANTY	
Product Warranty Period (Worldwide)	1-year limited warranty

© 2017 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies:

<https://www.tripplite.com/products/product-certification-agencies>