

Features:

Motor: External Rotor Capacitor-Run Induction Motor

• Motor Protection: Thermal Protected

• Bearing Type: Two Ball · Connection: Terminal Block

• Frame Material: Aluminum Alloy

• Impeller Material: Steel

IP56M Certified

• Operating Temp:

Two Ball: -20°C~70°C

Life Expectancy:

Two Ball: 50,000 Hours Two Ball: 100,000 Hours (-L)

an-S Division







Model No.	Volt.	Freq.	Current	Power	Rated Speed	Maximum AirFlow		Maximum Static Pressure		Noise Level	Weight
	(VAC)	(Hz)	(A)	(W)	(rpm)	(CMM)	(CFM)	(InAq)	(mmAq)	(dB/A)	(g)
FDA2-22580NBHK4D #	115	50/60	0.61/0.62	53.0/68.0	2800/3200	16.4/19.0	580/670	0.925/0.807	23.5/20.5	68.0/71.0	2750
FDA2-22580QBHK4D#	230	50/60	0.26/0.31	53.0/68.0	2800/3200	16.4/19.0	580/670	0.925/0.807	23.5/20.5	68.0/71.0	2750

Indicates "-L" (100,000 Hours Life Expectancy) or Leave Blank (50,000 Hours Life Expectancy)

Noise is measured at the distance of one (1) meter from the axis of intake.

