

## PRODUCT DATASHEET Cute series

last update 26/6/2013

	Product number	C10446_CUTE-4-SS		
	Family	Cute	FWHM	11 degrees
	Туре	Lens array	Efficiency	88 %
	LED	XR-E	cd/lm	13.200
A MARKEN AND A MARKEN A	Color	Clear	Gerber File	Available
	Diameter	35 mm		
	Height	15 mm		
	Style	Round		
	Optic Material	PMMA		
	Holder Material	-		
	Fastening	["pin", "glue"]		
	Status	Production ready		
	Product number	C10447_CUTE-4-M		
	E a sea 'lla a	0.4		10 10 10 10 10
	Family -	Cute	FWHM	18 degrees
	Туре	Lens array	Efficiency	84 %
	LED	XR-E	cd/lm	4.260
The second second	Color	Clear	Gerber File	Available
	Diameter	35 mm		
	Height	15 mm		
	Style	Round		
	Optic Material	PMMA		
FUT ENSIN	Holder Material	-		
	Fastening	["pin", "glue"]		
	Status	Production ready		

NOTE: The typical divergence will be changed by different color, chip size and chip position tolerance. The typical total divergence is the full angle measured where the luminous intensity is half of the peak value.

Ledil Oy Salorankatu 10 24240 SALO Finland



## **GENERAL INFORMATION**


- Product series especially designed & optimized for XR-E series of LEDs.

- Special care taken to make light distribution as uniform as possible.


- Lens material optical grade PMMA with high UV and temperature resistance. Allows use of high current and temperature conditions.

Please find more information about used material from below:


http://ledil.fi/sites/default/files/Documents/Technical/Material/PMMA%208N%20UL94\_Yellow%20Card.pdf http://ledil.fi/sites/default/files/Documents/Technical/Material/PMMA%208N%20PLEXIGLAS-Datasheet.pdf Relative intensity of C10447\_Cute-4-M




## Luminaire: Ledil Oy 10446\_Cute-4-SS 10446\_Cute-4-SS Lamps: 1 x Cree XR-E 4PCB (white)







Luminaire: Ledil Oy 10446\_Cute-4-SS 10446\_Cute-4-SS Lamps: 1 x Cree XR-E 4PCB (white)



C0 - C180 - C90 - C270

Luminaire: Ledil Oy 10447\_Cute-4-M 10447\_Cute-4-M Lamps: 1 x Cree XR-E 4PCB (white)

