Apr.1.2017 Copyright 2017 HIROSE ELECTRIC CO., LTD. All Rights Reserved.

| APPLICABLE STANDARD | | | | |
|---|---|---|---|---|
| RATING | OPERATING TEMPERATURE RANGE | -35 °C TO +85 °C(NOTES 1) | STORAGE TEMPERATURE RANGE | -10 °C TO +60 °C |
| | VOLTAGE | 30V AC | APPLICABLE CONNECTOR | DF30*-*DP-0.4V(**) |
| | CURRENT | 0.3A | | |

# SPECIFICATIONS

| ITEM | TEST METHOD | REQUIREMENTS | QT | AT |
|---|---|---|---|---|
| **CONSTRUCTION** | | | | |
| GENERAL EXAMINATION | VISUALLY AND BY MEASURING INSTRUMENT. | ACCORDING TO DRAWING. | X | X |
| MARKING | CONFIRMED VISUALLY. | | X | X |
| **ELECTRIC CHARACTERISTICS** | | | | |
| CONTACT RESISTANCE | 100m A (DC OR 1000 Hz). | 100mΩ MAX. | X | — |
| INSULATION RESISTANCE | 100V DC. | 50MΩ MIN. | X | — |
| VOLTAGE PROOF | 100V AC FOR 1 min. | NO FLASHOVER OR BREAKDOWN. | X | — |
| **MECHANICAL CHARACTERISTICS** | | | | |
| MECHANICAL OPERATION | 50 TIMES INSERTIONS AND EXTRACTIONS. | ① CONTACT RESISTANCE: 100mΩ MAX.<br>② NO DAMAGE, CRACK OR LOOSENESS OF PARTS. | X | – |
| VIBRATION | FREQUENCY 10 TO 55 Hz, SINGLE AMPLITUDE 0.75 mm, 10 CYCLES OF EACH 3 AXIAL DIRECTION FOR 5 min. | ① NO ELECTRICAL DISCONTINUITY OF 1 μs.<br>② NO DAMAGE, CRACK OR LOOSENESS OF PARTS. | X | – |
| SHOCK | 490 $m/s^2$ DURATION OF PULSE 11 ms AT 3 TIMES FOR 3 DIRECTIONS. | ① NO ELECTRICAL DISCONTINUITY OF 1 μs.<br>② NO DAMAGE, CRACK OR LOOSENESS OF PARTS. | X | – |
| **ENVIRONMENTAL CHARACTERISTICS** | | | | |
| RAPID CHANGE OF TEMPERATURE | TEMPERATURE -55→ 5 TO 35→+85→ 5 TO 35 °C<br>TIME 30→10 TO 15→30→10 TO 15min<br>UNDER 5 CYCLES. | ① CONTACT RESISTANCE: 100mΩ MAX.<br>② INSULATION RESISTANCE: 50MΩ MIN.<br>③ NO DAMAGE, CRACK OR LOOSENESS OF PARTS. | X | – |
| DAMP HEAT (STEADY STATE) | EXPOSED AT 40 ± 2 °C, 90 TO 95 %, 96 h. | ① CONTACT RESISTANCE: 100mΩ MAX.<br>② INSULATION RESISTANCE: 25MΩ MIN.<br>③ NO DAMAGE, CRACK OR LOOSENESS OF PARTS. | X | – |
| CORROSION SALT MIST | EXPOSED IN 5% SALT WATER SPPAY FOR 48h.<br>(TEST STANDARD: IEC60068) | ① CONTACT RESISTANCE: 100mΩ MAX.<br>② NO HEAVY CORROSION. | X | – |
| SULPHUR DIOXIDE | EXPOSED IN 25 PPM FOR 96h.<br>(TEST STANDARD: IEC60068) | ① CONTACT RESISTANCE: 100mΩ MAX.<br>② NO HEAVY CORROSION. | X | – |

| | COUNT | DESCRIPTION OF REVISIONS | DESIGNED | CHECKED | DATE |
|---|---|---|---|---|---|
| 0 | | | | | |

REMARKS
NOTE1: INCLUDE THE TEMPERATURE RISING BY CURRENT

Unless otherwise specified, refer to IEC60512.

| | | |
|---|---|---|
| APPROVED | MO.NAKAMURA | 05.09.30 |
| CHECKED | TS.MIYAZAKI | 05.09.29 |
| DESIGNED | AR.TAKAHASHI | 05.09.29 |
| DRAWN | AR.TAKAHASHI | 05.09.29 |

Note QT:Qualification Test AT:Assurance Test X:Applicable Test

DRAWING NO. ELC4-303547-04

| | | | | |
|---|---|---|---|---|
| HRS | SPECIFICATION SHEET | PART NO. | DF30FB-*DS-0.4V(82) | |
| | HIROSE ELECTRIC CO., LTD. | CODE NO. | CL684-****-*-82 | 0 1/ |

FORM HD0011-2-1