

596-16822

HellermannTyton

Article Number: 596-16822

Description: Thermal Transfer Labels, .90" x .25", 3 Across, Polyester, White, 10,000/roll



Base Data	
Local Order Number	TAG16T3-822
Type	TAG16T3
Color	White (WH)
Features and benefits	<ul style="list-style-type: none"> • Thermal transfer labels are made with high performance materials for long term industrial applications. • Labels can be printed in any standard thermal transfer printer giving the user options for printing and eliminating the need to be dedicated to one printer model. • The labels are available in a wide variety of sizes so that finding a label for a particular application is easy.
Quantity Per	reel
Product Description	Labels are made with various high performance materials including polyester, metalized polyester, clear polyester, cloth, polyimide and the Durattach label stock. The construction includes an aggressive acrylic adhesive and abrasion and chemical resistant top coatings that are made to accept ink from a thermal transfer printer. The product is supplied on rolls on a 3" cardboard core.
Short Description	Thermal Transfer Labels, .90" x .25", 3 Across, Polyester, White, 10,000/roll
Product Dimensions	
Width W (Imperial)	0.90"
Width W (Metric)	22.8mm
Height H (Imperial)	0.25"
Height H (Metric)	6.35mm
Horizontal Repeat HR (imperial)	0.90"
Horizontal Repeat HR (metric)	22.86mm
Print Method	Thermal transfer
Vertical Repeat VR (imperial)	0.35"
Vertical Repeat VR (metric)	8.89mm
Width of Liner WL (imperial)	3.35"
Width of Liner WL (metric)	85.09mm

596-16822



Material and Specifications		
	Material	Type 822, Polyester, white (WH)
	Material Shortcut	822
	Adhesive Operating Temperature	-40°F to +302°F (-40°C to +150°C)
	Operating Temperature	-40°F to +302°F (-40°C to +150°C)
	ROHS Compliant	Yes
	Certification/Specification	UL-Recognized
	UL Recognized (US and Canada)	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	10000
	Package Quantity (Metric)	10000
	Customs Number(Schedule B)	3919102055
	Labels per Row	3
	Weight (Metric)	0.471kg