

151-00756

Article Number: 151-00756



Description: High-Torque Double Mnt, 4-Way, .38" Mounting Hole, 114 lb-ft Max Torque, PA66HIRHSUV, Black, 100/pkg

Base Data	Local Order Number	151-00756
	Type	HDM375BDM4W
	Color	Black (BK)
	Features and Benefits	<ul style="list-style-type: none"> <li>• Arched "H" profile surface allows for broad surface contact with the bundle, minimizing pinching and crushing of the bundles.</li> <li>• High Torque metal bushing allows for strength in heavy duty applications.</li> <li>• These mounts contain a small tab inside the mounting hole to temporarily engage the threads which allows assemblers to pre-install the mount on a stud with a washer and nut.</li> </ul>
	Quantity Per	bag
	Product Description	High Torque Double Mounts are designed for routing multiple bundles with HellermannTyton heavy duty T250, T255, and wide strap cable ties to harness wires and hoses; however, they accept all standard cable ties up to .5" wide.
	Short Description	High-Torque Double Mnt, 4-Way, .38" Mounting Hole, 114 lb-ft Max Torque, PA66HIRHSUV, Black, 100/pkg
Product Dimensions	Length L (Metric)	89.0mm
	Fixation Method	Screw Mounting and Rivet
	Width W (Imperial)	1.4"
	Width W (Metric)	34.5mm
	Cable Tie Width Max. (Imperial)	0.5"
	Cable Tie Width Max. (Metric)	12.7mm
	Height H (Imperial)	1.0"
	Height H (Metric)	25.2mm
	Mounting Hole Diameter D (Imperial)	0.4"
	Mounting Hole Diameter D (Metric)	10.29 mm
Material and Specifications		
	Material	Polyamide 6.6 high impact modified, heat and UV-resistant (PA66HIRHSUV)

151-00756



Material and Specifications	Material Shortcut	PA66HIRHSW
	Flammability	UL 94 HB
	Maximum Torque (kgf-cm)	1576kgf-cm
	Maximum Torque (lbf-ft)	114lbf-ft
	Operating Temperature	-40°F to +221°F (-40°C to +105°C)
	REACH Compliant (Article 33)	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	100
	Package Quantity (Metric)	100Pieces
	Customs Number(Schedule B)	3926909987
	Content Unit (BMEcat)	pieces