

103-00002

Article Number: 103-00002

Description: Cable Tie for AT2060, 30lb Tensile Strength, PA66, Natural, 30/bandolier, 600/pkg



Base Data	
Local Order Number	T30RA30
Type	T30RA
Color	Natural (NA)
Features and Benefits	<ul style="list-style-type: none"> The AT2060 cable tie system is designed for automatic installation on bundles up to 1.25" and a minimum tensile strength of 30 lbs. Available in reels of 3,000 each or bandoliers of 30 each.
Quantity Per	bag
Product Description	Cable ties for use with HellermannTyton's AT2060 automatic cable tie tool
Short Description	Cable Tie for AT2060, 30lb Tensile Strength, PA66, Natural, 30/bandolier, 600/pkg
Product Dimensions	
Minimum Tensile Strength (Imperial)	30.0lbs
Minimum Tensile Strength (Metric)	135.0N
Length L (Imperial)	6.0"
Length L (Metric)	152.0mm
Cycle Time	1.2 seconds
Identification Plate Position	none
Reel Diameter (Imperial)	17.7"
Reel Diameter (Metric)	450mm
Reel Width (Imperial)	7.197"
Reel Width (Metric)	182.8m
Releasable Closure	No
Voltage Range	27 Volt
Width W (Imperial)	0.14"
Width W (Metric)	3.6mm
Bundle Diameter Min. (Imperial)	0.06"
Bundle Diameter Min. (Metric)	1.5mm

103-00002



Product Dimensions	Bundle Diameter Max. (Imperial)	1.25"
	Bundle Diameter Max. (Metric)	31.0mm
	Power Supply	Electrical
	Tension Force	Adjustable
Material and Specifications		
	Material	Polyamide 6.6 (PA66)
	Material Shortcut	PA66
	US MILSPEC	MS3367-5-9
	Flammability	UL 94 V2
	Operating Temperature	-40°F to +185°F (-40°C to +85°C)
	Certification/Specification	UL-ZODZ2.E64139
	UL Recognized (US and Canada)	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	600
	Package Quantity (Metric)	600
	Customs Number(Schedule B)	3926909987
	Reel Weight (Imperial)	7lbs
	Reel Weight (Metric)	3.175kg
	Weight (imperial)	3.9lbs