Material	High Conductivity Seamless Copper Tube	
Plating	Electro-Tin	
Wire Size	1/0 AWG	A D S S S C C C S S S C C C C S S C C C C
Wire Type	Stranded Copper; Class B: Compact, Compressed or Concentric, Class C: Concentric	PANDUT 1/0 STR CU 1/0 STR CU
Wire Strip Length	1-1/2 in.	.47±.04
Stud Size	1/2 in.	1 .47 1.04
UL Listed Wire Connector	Yes, for applications up to 35kv. Consult cable manufacturer for voltage stress relief instructions with applications greater than 2000 volts.	1.07±.04 —
UL Temperature Rating	90° C	
C.S.A Certified Wire Connector	Yes	.12±.01 — 90°±5°
Panduit Color Code on Barrel	PINK	2.14
Panduit Die Index No. on Barrel	P42	REF PANDUIT
Alternate Industry Die Index No. () on Barrel	(12)	1.44±.04
CERTIFIE	D LISTED Wire Connector	.39±.01 ————————————————————————————————————

						CORP. TINLEY PARK, ILLINOIS
00	9/02	SAB	DRL	RELEASED	10329	LCB1/0-12F-X Copper Lug - One-Hole, Long Barrel, 90° Angle Tongue
REV	DATE	BY	СНК	DESCRIPTION	ECN	SCALE N/A DRAWING NO / CAD FILE LCB1_0-12F-CUST