

151-00378



Article Number: 151-00378

Description: Automatic Harness Clip, Connectable, 1.1" Bundle Max, PA66HIRHS, Black, 500/pkg

| | | |
|---------------------------------|-----------------------|---|
| Base Data | Local Order Number | 151-00378 |
| | Type | IAHC3AH |
| | Color | Black (BK) |
| | Features and benefits | <ul style="list-style-type: none"> • Clips can be connected to each other to create a chain of cable harnesses. • Secures firmly to surfaces to eliminate moisture and corrosion. • Quick and easy installation ideal for the production environment. |
| | Quantity Per | carton |
| | Product Description | Automatic Harness Clips offer a simple and secure method of attaching cables to panels and other surfaces. When the cable is pushed inside, it automatically activates the locking features which causes it to close. These are also connectable which allows for multiple cables to be positioned next to each other. These come in various sizes to fit different bundle diameters. |
| | Short Description | Automatic Harness Clip, Connectable, 1.1" Bundle Max, PA66HIRHS, Black, 500/pkg |
| | Product Dimensions | Length L (Imperial) |
| Length L (Metric) | | 40.0mm |
| Length L2 (Imperial) | | 0.28" |
| Length L2 (Metric) | | 7.5mm |
| Width W (Imperial) | | 0.4" |
| Width W (Metric) | | 13.5mm |
| Height H (Imperial) | | 2.5" |
| Height H (Metric) | | 64.5mm |
| Bundle Diameter Min. (Imperial) | | 0.75" |
| Bundle Diameter Min. (Metric) | | 19.0mm |
| Bundle Diameter Max. (Imperial) | | 1.1" |
| Bundle Diameter Max. (Metric) | | 28.0mm |
| Disc Diameter (Imperial) | | 0.94" |
| Disc Diameter (Metric) | | 24.0mm |

151-00378



| | | |
|-----------------------------|-------------------------------------|---|
| Product Dimensions | Panel Thickness Max. (Imperial) | 0.03" |
| | Panel Thickness Max. (Metric) | 2.7mm |
| | Panel Thickness Min. (Imperial) | 0.04" |
| | Panel Thickness Min. (Metric) | 0.7mm |
| | Mounting Hole Diameter D (Imperial) | 0.24 - 0.26" |
| | Mounting Hole Diameter D (Metric) | 6.2 - 6.7 mm |
| Material and Specifications | | |
| | Material | Polyamide 6.6 high impact modified, heat stabilized, UV resistant (PA66HIRHS) |
| | Material Shortcut | PA66HIRHS |
| | Flammability | UL 94 HB |
| | Operating Temperature | -40°F to +221°F (-40°C to +105°C) |
| | REACH Compliant (Article 33) | Yes |
| | ROHS Compliant | Yes |
| Logistic and Packaging | | |
| | Package Quantity (Imperial) | 500 |
| | Package Quantity (Metric) | 500Pieces |
| | Customs Number(Schedule B) | 3926909987 |
| | Content Unit (BMEcat) | pieces |