

Printed-circuit board connector - ZEC 1,0/ 2-ST-3,5 C1 R1GYNZ108 - 1992298

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)

Direct connector, Nominal current: 8 A, Number of positions: 2, Pitch: 3.5 mm, Connection method: Spring-cage connection, Color: Gray, Contact surface: Tin

Key commercial data

| Packing unit | 1 pc |
|------------------------|----------|
| Minimum order quantity | 50 pc |
| Custom tariff number | 85366990 |
| Country of origin | Germany |

Technical data

Dimensions

| Pitch | 3.5 mm |
|-------------|--------|
| Dimension a | 3.5 mm |

General

| Range of articles | ZEC 1,0/ST |
|----------------------------------|-------------------|
| Rated voltage (III/3) | 160 V |
| Connection in acc. with standard | EN-VDE |
| Nominal current I _N | 8 A |
| Nominal cross section | 1 mm ² |
| Number of positions | 2 |

Connection data

| Conductor cross section solid min. | 0.2 mm ² |
|--|----------------------|
| Conductor cross section solid max. | 1 mm ² |
| Conductor cross section stranded min. | 0.2 mm² |
| Conductor cross section stranded max. | 1 mm ² |
| Conductor cross section stranded, with ferrule without plastic sleeve min. | 0.25 mm ² |
| Conductor cross section stranded, with ferrule without plastic sleeve max. | 1 mm ² |
| Conductor cross section stranded, with ferrule with plastic sleeve min. | 0.25 mm ² |
| Conductor cross section stranded, with ferrule with plastic sleeve max. | 0.75 mm² |
| Conductor cross section AWG/kcmil min. | 24 |
| Conductor cross section AWG/kcmil max | 16 |



Printed-circuit board connector - ZEC 1,0/ 2-ST-3,5 C1 R1GYNZ108 - 1992298

Technical data

Connection data

| 2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, min. | |
|---|---------------------|
| 2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, max. | 0.5 mm ² |
| Minimum AWG according to UL/CUL | 26 |
| Maximum AWG according to UL/CUL | 16 |

Classifications

eCl@ss

| eCl@ss 4.0 | 272607xx |
|------------|----------|
| eCl@ss 4.1 | 27260701 |
| eCl@ss 5.0 | 27260701 |
| eCl@ss 5.1 | 27260701 |
| eCl@ss 6.0 | 27260704 |
| eCl@ss 7.0 | 27440402 |
| eCl@ss 8.0 | 27440309 |

ETIM

| ETIM 3.0 | EC001121 |
|----------|----------|
| ETIM 4.0 | EC002637 |
| ETIM 5.0 | EC002637 |

UNSPSC

| UNSPSC 6.01 | 30211810 |
|---------------|----------|
| UNSPSC 7.0901 | 39121409 |
| UNSPSC 11 | 39121409 |
| UNSPSC 12.01 | 39121409 |
| UNSPSC 13.2 | 39121409 |

Phoenix Contact 2014 @ - all rights reserved http://www.phoenixcontact.com