8-28-06

В

Date:

Revision:



120 OHM, AWG 26, 19 STRANDS OF AWG 38, RADIO FREQUENCY, TWO CONDUCTOR CABLE

THIS SPECIFICATION SHEET FORMS A PART OF THE LATEST ISSUE OF RAYCHEM SPECIFICATION 1200.

CONSTRUCTION **DETAILS** DIMENSIONS ARE NOMINAL VALUES IN INCHES UNLESS OTHERWISE **CONDUCTORS** AWG 26, 19 Strands of .020 AWG 38, Silver-Coated High Strength Copper Alloy **DIELECTRICS** .047 Rayfoam® H Colors - White/Light Blue **FILLERS** .031 Radiation-Crosslinked Modified ETFE JACKET FLAWS **SHIELD** .101 Flat, .0015 inch thick Tin-Coated Copper COLD BEND

JACKET

Modified FEP

Outer jacket will be white (designated by a "-9" appended to the part number, e.g., 2026G2424-9) unless otherwise specified.

Designate outer jacket color with a dash number in accordance with MIL-STD-681. Other codes and suffixes may be added to the part number, as necessary, to capture any additional requirements imposed by the purchase order.

ELECTRICAL CHARACTERISTICS

CHARACTERISTIC IMPEDANCE 120 ± 10 ohms, Method D at 1 MHz

CAPACITANCE - MUTUAL 12.7 pF/ft. (nominal) 18.2 pF/ft. (maximum)

VELOCITY OF PROPAGATION 77% (nominal)

ADDITIONAL REQUIREMENTS

ELECTRICAL

CONDUCTOR RESISTANCE 42.0 ohms/1000 ft. (nominal) **INSULATION RESISTANCE** 10,000 megohms (minimum)

for 1000 ft.

SPARK TEST 1.0 kV (rms) **IMPULSE TEST** 6.0 kV (peak)

VOLTAGE WITHSTAND

(DIELECTRIC) 1500 volts (rms) (minimum)

ENVIRONMENTAL

FLAMMABILITY Method B **HEAT SHOCK** 225°C

-55°C/3.25 inch mandrel LOW TEMPERATURE-

VOLTAGE WITHSTAND

(POST ENVIRONMENTAL) 1000 volts (rms), 1 minute

PHYSICAL

INSULATION (DIELECTRIC)

(Prior to Cabling)

ELONGATION 50%(minimum) **TENSILE STRENGTH** 600 lbf/in2 (minimum)

JACKET

ELONGATION TENSILE STRENGTH JACKET THICKNESS SHIELD COVERAGE

200%(minimum) 2000 lbf/in² (minimum) .007 inch (nominal) 92%(minimum)

WEIGHT 9.8 lbs/1000 ft. (nominal)

Users should evaluate the suitability of this product for their application. Specifications are subject to change without notice.

Tyco Electronics also reserves the right to make changes in materials or processing, which do not affect compliance with any specification, without notification to Buyer.



.115