



**Tripp Lite**  
1111 West 35th Street  
Chicago, IL 60609 USA  
Telephone: +(773) 869 1234  
E-mail: [saleshelp@tripplite.com](mailto:saleshelp@tripplite.com)

## Model #: BP36V42-3U

### BP36V42-3U - External Battery Pack for UPS System

#### Highlights

- Extends runtime of select compatible Tripp Lite UPS Systems with 36V DC external battery connector
- Provides daisy-chain compatibility for multiple connected battery packs
- Simple installation; 3U rackmount, tower and stack adaptable



#### Description

BP36V42-3U rack/tower external battery pack offers extended battery runtime when used in conjunction with compatible Tripp Lite systems. Multi-use form factor supports configuration in stacking, upright tower and rackmount applications using only 3 rack spaces (3U). Includes heavy gauge cabling with high current DC connector for simple installation. Additional output connector allows multiple BP36V42-3U battery packs to be daisy-chained to the UPS for even longer extended run operation.

Compatible UPS systems - SMART1500RML2Ua, SMX1500RTXL2U and other Tripp Lite UPS systems that specify the use of this battery pack.

#### Applications

- Ideal means of lengthening the battery runtime provided by compatible Tripp Lite UPS systems. Battery pack may be ordered at time of original UPS purchase or sourced at a later date to extend runtime performance if site power conditions deteriorate and longer battery runtime is desired.

#### Package Includes

- External battery pack
- Mounting hardware
- Warranty information
- Instruction manual

#### Features

- Offers extended-run UPS operation when used in conjunction with compatible Tripp Lite UPS systems
- Supports stacking or rackmount installation using only 3 rack spaces (3U)
- Includes heavy gauge cabling with high current DC connectors for simple installation
- Attractive all-black color scheme
- Additional output connector allows multiple battery packs to be daisy-chained to the UPS for even longer extended run operation

#### Specifications

BATTERY	
Expandable battery runtime	Includes a second input/output connector to daisy-chain multiple battery packs

DC system voltage (VDC)	36
Connects to UPS via	Detachable cable with UPS specific DC connector (36 in length, 6 gauge)
Typical battery lifespan	4-6 years typical (North America)
<b>PHYSICAL</b>	
Shipping weight (lbs)	165.35
Shipping weight (kg)	75.1
Unit Dimensions (HWD/in)	5.25 x 17.5 x 25
Unit Dimensions (HWD/cm)	13.3 x 44.45 x 63.5
Shipping Dimensions (HWD/in)	11.25 x 23 x 31.5
Shipping Dimensions (HWD/cm)	28.6 x 58.42 x 80.01
Unit weight (lbs)	127.87
Unit weight (kg)	58.1
Material of construction	Steel
Form factors supported	3U rack/tower
<b>WARRANTY</b>	
Product Warranty Period (U.S. & Canada)	2-year limited warranty
Product Warranty Period (International)	1-year limited warranty
Product Warranty Period (Mexico)	1-year limited warranty
Product Warranty Period (Puerto Rico)	1-year limited warranty
Optional Coverage	3 and 5 year warranty extensions available

## Related Items

### Optional Products

Related Model	Description	Qty.
<a href="#">WEXT3-BP36V</a>	3-Year Extended Warranty - For All 36V Battery Packs	1
<a href="#">WEXT5-BP36V</a>	5-Year Extended Warranty - For All 36V Battery Packs	1
<a href="#">2-9USTAND</a>	Enables Tower Placement of Rackmount UPS Systems	1
<a href="#">2POSTRMKITHD</a>	Enables 2-Post Rackmount Installation of 3U and Larger UPS, Transformer and Battery Pack Components	1

More information, including related products, owner's manuals, and additional technical specifications, can be found online at [www.tripplite.com/en/products/model.cfm?variables.txtModelID=3018](http://www.tripplite.com/en/products/model.cfm?variables.txtModelID=3018).