APPLICA	BLE STANI	DARD									
OPERATING TEMPERATUR		E DANICE	E -55 °C TO 85 °C		STORAGE TEMPERATURE RANG		Ţ	-10 °C TO 60 °C ⁽³⁾			
RATING	VOLTAGE				OPERATING				40 % TO 80 %		
RATING			100 V AC			RANGE STORAGE HUN					
	CURRENT		0.4 A RAN								
		SPECIFICATION				S					
ITEM		TEST METHOD				REQUIREMENTS			QΤ	AT	
CONSTRU		NACHALI	V AND DV MEACHDING IN	OTDLINA		4000	DINO 3	- DE	ANAGNIC		
MARKING	XAMINATION	VISUALLY AND BY MEASURING INSTRUMENT. CONFIRMED VISUALLY.				ACCO	RDING	IO DE	AWING.	×	×
	C CHARAC									^	
CONTACT RESISTANCE						80 mΩ MAX . ⁽¹⁾				×	l –
CONTACT RESISTANCE		20 mV MAX, 1 mA(DC OR 1000Hz)				100 mΩ MAX . ⁽²⁾				×	-
MILLIVOLT LEVEL											
METHOD INSULATION		ora v Do									
RESISTANCE		250 V DC.				100 MΩ MIN.				×	-
VOLTAGE PROOF		300 V AC FOR 1 min.				NO FLASHOVER OR BREAKDOWN.					-
	CAL CHAR										
MECHANICAL OPERATION		50 TIMES INSERTIONS AND EXTRACTIONS.			NS.	① CONTACT RESISTANCE: 100 mΩ MAX. ⁽²⁾ ② NO DAMAGE, CRACK AND LOOSENESS OF PARTS.				×	_
VIBRATION		FREQUENCY 10 TO 55 Hz,				① NO ELECTRICAL DISCONTINUITY OF X					-
		AMPLITUDE: 1.5 mm,				1 μs.					
		AT 2 h FOR 3 DIRECTION.				② CONTACT RESISTANCE: 100 mΩ MAX.(2)					
SHOCK		490 m/s ² , DURATION OF PULSE 11 ms AT 3 TIMES FOR 3 DIRECTIONS.				③ NO DAMAGE, CRACK AND LOOSENESS OF PARTS.					-
ENVIRON	MENTAL C		TERISTICS	10110.		<u> </u>	7,1110.				
DAMP HEAT		EXPOSED AT 40±2 °C, 90 ~ 95 %, 96 h.				① COI	NTACT	RESIS	STANCE: 100 mΩ MAX. ⁽²⁾	×	l –
(STEADY STATE)						\oslash INSULATION RESISTANCE: 100 M Ω MIN.					
RAPID CHANGE OF TEMPERATURE		TEMPERATURE-55 \rightarrow +15 \sim +35 \rightarrow +85 \rightarrow +15 \sim +35 $^{\circ}$ C TIME 30 \rightarrow 2 \sim 3 \rightarrow 30 \rightarrow 2 \sim 3 min UNDER 5 CYCLES.				③ NO DAMAGE, CRACK AND LOOSENESS OF PARTS.					_
CORROSION SALT MIST		EXPOSED IN 5 % SALT WATER SPRAY FOR 48 h.				① CONTACT RESISTANCE: 100 mΩ MAX. (2) ② NO HEAVY CORROSION.				×	_
HYDROGEN SULPHIDE		EXPOSED IN 3 PPM FOR 96 h. (TEST STANDARD: JEIDA-38)								×	-
RESISTANCE TO		1) REFLOW SOLDERING : 250 °C MAX,				NO DEFORMATION OF CASE OF EXCESSIVE LOOSENESS OF THE TERMINALS.					-
SOLDERING HEAT		: 220 °C MIN, FOR 60 s 2) SOLDERING IRONS : 360 °C,									
		FOR 5 s									
SOLDERABILITY		SOLDERED AT SOLDER TEMPERATURE,							COATING OF SOLDER		-
		240 ± 3°C, FOR IMMERSION DURATION, 3 s.							MINIMUM OF 95 % OF EING IMMERSED.		
		TOK IMMERSION BOKATION, 5 s.				THE SORT ACE BEING IMMERSED.					
1 0011	T 5:	-copiet:	ON OF BEVIOLONG		DECLO	L			CHECKED	D. 4	<u></u>
COUN	i Di	=9CKIPH	ON OF REVISIONS		DESIG	יוו⊏ט			CHECKED	DA	1 =
<u>A</u>								1			
REMARK	IECTOR'S INITI	AL CONTAC	.L CONTACT RESISTANCE SHALL BE 80 mΩ,BECAUSE				APPRO	VED	HS.OKAWA	05.11.09	
BULK RE	SISTANCE OF S	FACKING HEIGHT 16 mm TYPE.			CHECK		KED) HS.OZAWA		1.08	
(3)THIS STOR	AGE INDICATE	S A LONG-	OF THE CONTACT RESISTANCE SHALL BE 20 m Ω MAX. A LONG-TERM STORAGE STATE FOR THE UNUSED PROJECT OF THE UNUS			ODUCT DESIGNE		NED	KY.NAKAMURA	05.11.08	
	HE BOARD MOU herwise spe		ified, refer to JIS C 5402.			DRAWN		ΝN	SY.KAMIGA	05.11.08	
					RAWING NO.			ELC4-150822-25			
HS	S	SPECIFICATION SHEET			PART NO.		FX8C-80P-SV (71)				
		ROSE ELECTRIC CO., LTD.			CODE	NO.	CL578-0503-4-71				1/1
FORM JIDOO11							_				_