APPLICA	BLE STA	NDARD										
	OPERATING		55.00 TO 05.0	20 (1)		RAGE			40.00 TO 60.0	0 (2)		
RATING	TEMPERATURE RANGE		-55 °C TO 85 °C (1)				JRE RANGE -10 °C TO 6 SHUMIDITY		-10 °C TO 60	0 °C (2)		
	VOLTAGE		125 V AC		RAN		HOMIDII	1	40 % TO 80	%		
	CURRENT		0.5 A			STRAGE HU RANGE			40 % TO 70 % ⁽²⁾			
	CONNENT											
	APPLICAB	PPLICABLE CABLE AWG #28 (JACKET SIZE : 0.9±0.1mm)										
			SPEC		ATION	<u>IS</u>						
ITEM			TEST METHOD			REQUIREMENTS				QT	AT	
CONSTRUCTION												
	XAMINATIO		VISUALLY AND BY MEASURING INSTRUMENT.				ACCORDING TO DRAWING.					
MARKING			CONFIRMED VISUALLY.									
			FERISTICS									
CONTACT R			100 mA (DC OR 1000 Hz).				45 mΩ MAX.				-	
CONTACT RESISTANCE		20 mV N	20 mV MAX, 1 mA(DC OR 1000Hz)				55 mΩ MAX .				-	
MILLIVOLT LEVEL METHOD												
INSULATION	l	250 V D	250 V DC				100 MΩ MIN.				1-	
RESISTANCE		0001/4										
							NO FLASHOVER OR BREAKDOWN.					
MECHANI INSERTION				NEOTO	<u> </u>	INCER	TION FO	DOT:	46 N MAX.	1 .		
WITHDRAW.			MEASURED BY APPLICABLE CONNECTOR.				NON FC			×	-	
MECHANICA			500 TIMES INSERTIONS AND EXTRACTIONS.						ANCE: 55 mΩ MAX.	×	+-	
OPERATION							② NO DAMAGE, CRACK AND LOOSENESS					
							OF PARTS.					
VIBRATION			FREQUENCY 10 TO 55 Hz,					RICAL [DISCONTINUITY OF	×	-	
			AMPLITUDE: 0.76 mm, AT 2 h FOR 3 DIRECTIONS.				1 μs. ② NO DAMAGE, CRACK AND LOOSENESS					
SHOCK			490 m/s ² , DURATION OF PULSE 11 ms				OF PARTS.				† <u>-</u> -	
			AT 3 TIMES FOR 3 DIRECTIONS.									
ENVIRON	MENTAL	CHARAC	TERISTICS			•						
DAMP HEAT		EXPOSE	EXPOSED AT 40±2 °C, 90 ~ 95 %, 96 h.				① CONTACT RESISTANCE: 55 mΩ MAX.					
(STEADY ST							② INSULATION RESISTANCE:100 MΩ MIN.				<u> </u>	
RAPID CHANGE OF TEMPERATURE			TEMPERATURE-55 \rightarrow +15 \sim +35 \rightarrow +85 \rightarrow +15 \sim +35 $^{\circ}$ C TIME 30 \rightarrow 10 \sim 15 \rightarrow 30 \rightarrow 10 \sim 15 min.				③ NO DAMAGE, CRACK AND LOOSENESS OF PARTS.				-	
TENNI EIGGIGE			UNDER 5 CYCLES.				FARIS.					
CORROSION SALT MIST							$\textcircled{1}$ CONTACT RESISTANCE: 55 m Ω MAX. $\textcircled{2}$ NO HEAVY CORROSION.					
		48 h.										
HYDROGEN SULPHIDE			EXPOSED IN 3 PPM FOR 96 h.							×	-	
		(IESI SI	(TEST STANDARD: JEIDA 38)								-	
COUN	T	DESCRIPTION	ON OF REVISIONS		DESIG	NED			CHECKED	DA	ATE	
<u> </u>												
			RISE INCLUDED WHEN ENERGIZED. INDICATES A LONG-TERM STORAGE STATE ED PRODUCT BEFORE THE BOARD MOUNTED.				APPRO	,		08.0	07. 01	
(.							CHEC	KED	HT. YAMAGUCHI	08. 07. 01		
						DESIGNED DRAWN		NED	KN. SHIBUYA	08. 07. 0		
Unless otherwise specified, r			efer to MIL-STD-1344.					VN_	AH. EDASHIGE	08. 06. 16		
Note QT:Qualification Test AT:Ass			urance Test X:Applicable Test			DRAWING NO.			ELC4-150661-00			
			CATION SHEET			PART NO.		FX2BA-52SA-1. 27R				
TCT TOTAL			LECTRIC CO., LTD.		CODE NO.		CL572-0674-9-00 Z			\wedge	1/1	
FORM HD0011-	0.1						I					