



**Tripp Lite**  
1111 West 35th Street  
Chicago, IL 60609 USA  
Telephone: +(773) 869 1234  
E-mail: [saleshelp@tripplite.com](mailto:saleshelp@tripplite.com)

## Model #: BP72V28RT-3U

### BP72V28RT-3U - External Battery Pack for UPS System

#### Highlights

- Extends the runtime of select compatible Tripp Lite UPS systems with 72VDC external battery connector
- Simple installation; 3U rackmount, tower and stack adaptable



#### Description

BP72V28RT-3U rack/tower external battery pack offers extended battery runtime when used in conjunction with compatible Tripp Lite systems. Multi-use form factor supports configuration in rackmount or stacking applications using only 3 rack spaces (3U). Upright tower configuration supported with optional 2-9USTAND accessory. Includes heavy gauge cabling with high current DC connector for simple installation. Additional DC connector enables the daisy-chaining of multiple external battery packs for longer extended run capability. COMPATIBLE UPS SYSTEMS - SMART3000RMOD2U, SU3000RTL2U, SU3000RTL3U, SU3000RTL3UHV, SU3000RTXR3U, SU3000RTXR3UHW, SUINT3000RTL2U, SUINT3000RTL3U, SU3000XL and other Tripp Lite UPS systems that specify the use of this battery pack.

#### Applications

- Ideal means of lengthening the battery runtime provided by compatible Tripp Lite UPS systems. Battery pack may be ordered at time of original UPS purchase or sourced at a later date to extend runtime performance if site power conditions deteriorate and longer battery runtime is desired.

#### Package Includes

- BP72V28RT-3U external battery pack
- Mounting hardware
- Warranty information
- Instruction manual

#### Features

- Offers extended-run UPS operation when used in conjunction with compatible Tripp Lite UPS systems
- Supports stacking or rackmount installation using only 3 rack spaces (3U)
- Supports upright tower installation with optional 2-9USTAND accessory (holds 3 battery packs in tower configuration)
- Includes heavy gauge cabling with high current DC connectors for simple installation

#### Specifications

BATTERY	
Expandable battery runtime	Yes, DC connector accepts daisy-chaining of multiple external battery packs for extended runtime operation
DC system voltage (VDC)	72
Connects to UPS via	Black 3-point DC connector

Typical battery lifespan	4-6 years typical
<b>PHYSICAL</b>	
Shipping weight (lbs)	164.8
Shipping weight (kg)	74.8
Unit Dimensions (HWD/in)	5.25 x 17.5 x 25
Unit Dimensions (HWD/cm)	13.33 x 44.45 x 63.5
Shipping Dimensions (HWD/in)	11.25 x 23 x 33
Shipping Dimensions (HWD/cm)	28.58 x 58.42 x 83.8
Unit weight (lbs)	148
Unit weight (kg)	66.6
Material of construction	Steel
Form factors supported	3U rack/tower
<b>WARRANTY</b>	
Product Warranty Period (U.S. & Canada)	2-year limited warranty
Product Warranty Period (International)	1-year limited warranty
Product Warranty Period (Mexico)	1-year limited warranty
Product Warranty Period (Puerto Rico)	1-year limited warranty

## Related Items

### Optional Products

Related Model	Description	Qty.
WEXT3-BP72V	3-Year Extended Warranty - For All 72V Battery Packs	1
WEXT5-BP72V	5-Year Extended Warranty - For All 72V Battery Packs	1
2-9USTAND	Enables Tower Placement of Rackmount UPS Systems	1
2POSTRMKITHD	Enables 2-Post Rackmount Installation of 3U and Larger UPS, Transformer and Battery Pack Components	1

More information, including related products, owner's manuals, and additional technical specifications, can be found online at [www.tripplite.com/en/products/model.cfm?variables.txtModelID=3130](http://www.tripplite.com/en/products/model.cfm?variables.txtModelID=3130).

Copyright © 2013 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.