

595-16400

# HellermannTyton

Article Number: 595-16400

Description: Dot Matrix Label, .90" x .25", 8 Across, Polyester, White, 5000/pkg



Base Data	
Local Order Number	TAG16-400
Type	TAG16
Color	White (WH)
Features and Benefits	<ul style="list-style-type: none"> <li>• Tabtag Dot Matrix labels are specifically made for use in dot matrix printers for fast and easy printing.</li> <li>• Labels come with a pin-feed margin to ensure that they can easily be loaded into any dot matrix printing system.</li> </ul>
Quantity Per	pack
Product Description	Used with dot matrix printers, HellermannTyton TabTags can be used for virtually any labeling application. Unless noted, TabTags are mounted on pinfed, fan-folded sheets for use with computers, word processors, or typewriters. Manufactured in a wide range of standard sizes and materials, the dot matrix printable TabTags can meet a wide variety of labeling requirements.
Short Description	Dot Matrix Label, .90" x .25", 8 Across, Polyester, White, 5000/pkg
Product Dimensions	
Length L (Imperial)	0.25"
Length L (Metric)	6.4mm
Width W (Imperial)	0.9"
Width W (Metric)	22.8mm
Height H (Imperial)	0.25"
Height H (Metric)	6.35mm
Height of printable area (metric)	6.40mm
Horizontal Repeat HR (metric)	25.40mm
Horizontal Repeat HR (imperial)	1.000"
Print Method	Dot-Matrix
Vertical Repeat VR (imperial)	0.333"
Vertical Repeat VR (metric)	8.45mm
Width of Liner WL (imperial)	8.9"

595-16400

# HellermannTyton

Product Dimensions	Width of Liner WL (metric)	226.00mm
Material and Specifications	Material	Type 400, Polyester, white (WH)
	Material Shortcut	400
	Adhesive	Acrylic
	Adhesive Operating Temperature	-40°F to +302°F (-40°C to +150°C)
	Minimum Application Temperature	from +50°F (from +10°C)
	Operating Temperature	-40°F to +302°F (-40°C to +150°C)
	ROHS Compliant	Yes
	Certification/Specification	UL-Recognized
Logistic and Packaging	Package Quantity (Imperial)	5000
	Package Quantity (Metric)	5000
	Customs Number(Schedule B)	3919905060
	Labels per Row	8
	Weight (Metric)	0.09kg