APPLICABLE STANDARD										
OPERATING TEMPERATURE RANGE		-35 °C TO +85 °C(NO	OTES 1)			<u> </u>	−10 °C TO +60 °C			
RATING VOLTAGE		30 V AC			APPLICABLE CONNECTOR			DF37*-34DP-0. 4V (**)		
CURRENT		0.3 A								
SPECIFICATIONS										
ITEM			TEST METHOD		REQUIREMENTS				АТ	
CONSTR	RUCTION									
GENERAL EXAMINATION VISUALLY			Y AND BY MEASURING INSTRUMENT.			ACCORDING TO DRAWING.				Х
			MED VISUALLY.							X
ELECTRIC CHARACTERIS										
CONTACT RESISTANCE 20 mV A			AC OR LESS 1khz,1m A .			100 mΩ MAX.				
INSULATION RESISTANCE		100 V DC.			50 M Ω	50 MΩ MIN.				_
VOLTAGE PROOF		100 V AC FOR 1 min.			NO FL	NO FLASHOVER OR BREAKDOWN.				
MECHA	NICAL CHA	RACTI	ERISTICS						X	
MECHANIC	AL		TIMES INSERTIONS AND EXTRACTIONS.			① CONTACT RESISTANCE: 100 mΩ MAX.				
OPERATION						② NO DAMAGE, CRACK OR LOOSENESS OF PARTS.				_
COUNT	II. DI		ON OF DEVISIONS		DESIGNED			CHECKED		
COUN	II DE	SCRIPTION OF REVISIONS		L	DESIGNED		CHECKED		DA	.IE
REMARKS						APPROVED CHECKED		KH. IKEDA	10. 03. 29	
NOTE1: INCLUDE THE TEMPERATURE I			RISING BY CURRENT					TS. MIYAZAKI	10. 03. 27	
						DESIGNED		RT. SHIMIZU	10. 03. 26	
Unless oth	erwise specif	ied, refer	to JIS C 5402.			DRAWN		RT. SHIMIZU	10. 03. 26	
Note QT:Qualification Test AT:Assurance Test X:Applicable Test					DRAWIN	RAWING NO. ELC4-330837			′-01	
HS	SF	PECIFI	ECIFICATION SHEET				DF37CJ-34DS-0. 4V (53)			
	HIR	OSE ELECTRIC CO., LTD.			ODE NO.	CL684-3086-5-53			▲	1/