APPLICAE	BLE STANI	DARD									
	OPERATING	E DANIGE	-55 °C TO 85 °		RAGE	IDE DAN	05	10 °C TO 60 °C (2)			
RATING	TEMPERATURE RANGE VOLTAGE CURRENT		-55 °C 10 65 °			URE RANGE  HUMIDITY		-10 °C TO 60 °C			
			125 V AC		RANG	GE			40 % TO 80 %	)	
			0.5 A	STORAGE H		JMIDITY 40 % TO 70 % (2			(2)		
	0011112111	SPECIFICATIONS									
	EM	I	TEST METHOD				D		DEMENTS	Тот	AT
CONSTRU		TEST METHOD				REQUIREMENTS					AI
		MEHALL	V AND BY MEASURING ING	STRUME	NT	ACCO	SDING .	TO DR	AWING.	Τ×	×
MARKING	O (WIII W) (TI OIV	VISUALLY AND BY MEASURING INSTRUMENT.  CONFIRMED VISUALLY.					(DIIVO	I O DI	, (VIIIVO.	×	×
ELECTRIC	CHARAC	TERISTICS								1	-1
CONTACT RESISTANCE		100 mA (DC OR 1000 Hz).					45 mΩ MAX .				_
CONTACT RESISTANCE MILLIVOLT LEVEL METHOD		20 mV MAX, 1 mA(DC OR 1000Hz)				55 mΩ MAX.				×	
INSULATION		250 V DC.					100 MΩ	2 MIN.		×	_
RESISTANCE											
VOLTAGE PR		300 V AC FOR 1 min.					ASHOVI	ER OR	BREAKDOWN.	×	_
	CAL CHAR			DACTION	10	(A) 001	NEAGE	DEGIG	TANOE SE OMAY	T	ı
MECHANICAL OPERATION		500 TIMES INSERTIONS AND EXTRACTIONS.				① CONTACT RESISTANCE: 55 mΩ MAX. ② NO DAMAGE, CRACK AND LOOSENESS OF PARTS.				×	_
VIBRATION SHOCK		FREQUENCY 10 TO 55 Hz,				① NO	ELECT	RICAL	DISCONTINUITY OF	×	_
		AMPLITUDE: 1.52 mm,				1 με					
		AT 2 h FOR 3 DIRECTION.  490 m/s², DURATION OF PULSE 11 ms					PARTS.		RACK AND LOOSENESS		<u> </u>
		AT 3 TIMES FOR 3 DIRECTIONS.				OF PARTS.					
ENVIRONI	MENTAL C	HARAC	TERISTICS								
DAMP HEAT		·				① CONTACT RESISTANCE: 55 mΩ MAX. × -					
(STEADY STATE)						② INSULATION RESISTANCE: 100 MΩ MIN. ③ NO DAMAGE, CRACK AND LOOSENESS OF PARTS.					
RAPID CHANGE OF TEMPERATURE		TEMPERATURE-55 $\rightarrow$ +15 $\sim$ +35 $\rightarrow$ +85 $\rightarrow$ +15 $\sim$ +35 $\circ$ C TIME 30 $\rightarrow$ 10 $\sim$ 15 $\rightarrow$ 30 $\rightarrow$ 10 $\sim$ 15 min UNDER 5 CYCLES.									-
		EXPOSED IN 5 % SALT WATER SPRAY FOR 48 h.				$\bigcirc$ CONTACT RESISTANCE: 55 m $\Omega$ MAX. $\bigcirc$ NO HEAVY CORROSION.				×	_
HYDROGEN SULPHIDE		EXPOSED IN 3 PPM FOR 96 h. (TEST STANDARD: JEIDA-38)									-
RESISTANCE TO		1) SOLDER BATH:SOLDER TEMPERATURE.				NO DEFORMATION OF CASE OF EXCESSIVE LOOSENESS OF THE TERMINAL.					_
SOLDERING HEAT		260±5°C FOR IMMERSION, DURATION, 10±1s.									
		2) SOLDERING IRONS : 360°C FOR 5 s.									
SOLDRABILITY		SOLDERED AT SOLDER TEMPERATURE				A NEW UNIFORM COATING OF SOLDER				×	-
		240±3°C FOR IMMERSION DURATION, 2s.				SHALL COVER A MINIMUM OF 95 % OF THE SURFACE BEING IMMERSED.					
COUN	Г ОІ	SCRIPTION	ON OF REVISIONS		DESIG	NED			CHECKED		\TE
<u> </u>											
	TEMPERATUR	RE RISE INC	SE INCLUDED WHEN ENERGIZED. DICATES A LONG-TERM STORAGE STATE PRODUCT BEFORE THE BOARD MOUNTED.  ed, refer to MIL-STD-1344.			APPROVED CHECKED DESIGNED DRAWN		OVED	HS. OKAWA		
	THIS STORAG	E INDICATE							HS. OZAWA		
	FUR THE UNL	IPEN KKOE							SY, KAMIGA	07. 12. 26	
Unless oth	nerwise spe	cified, re							HK. SUNADOR I		
					RAWING NO. ELC4-150649-						
		PECIFICATION SHEET				ART NO.		FX2BA-68PA-1. 27DSA (7			
<b>HS</b>	HIR	OSE ELECTRIC CO., LTD.			CODE	NO.	CL572-0926-0-71				1/1