

SUMMARY

Wires

Low	0
High	0
Coax	0
Triax	0
Quad	0
Fiber	0
Fluidic	0

Image is for illustrative purpose only

Download

[Request a quote](#)

[Catalog](#)

Series	3S
Termination type	No contacts / Accessory
IP rating	0
Cable Ø	8.10 - 9.00 mm
Matching parts	xxx

TECHNICAL DETAILS

Mechanics

Shell Style/Model	GSC*: Lead through with cable collet
Keying	
Housing Material	Brass (nickel plated) shell, collet nut, latch sleeve and mid pieces
Cable Fixing	∅ 8.1 - 9 mm
Variant	

Performance

Configuration	3S.290 : no contacts
Insulator	
Rated Current	

Others

Temp (min / max):	-55° C / +250° C
Humidity (max):	<=95% [at 60 deg C / 140 F]
Vibration:	15 g [10 Hz - 2000 Hz]
Shock Resistance:	100 g [6 ms]
Salt Spray Corrosion:	>1000 hr

Climatical Category: 50/175/21
Shielding (min): 75 dB (10 MHz)
Shielding (min): 40 dB (1 GHz)
IP Rating: 0

DRAWINGS

Draws

Dimensions

	A	B	E	L	M	S1	S2	S3	e
mm.	17	19.5	8.1	30	12	â??	14	17	M15x1.0
in.	0,67	0,77	0,32	1,18	0,47		0,55	0,67	

RECOMMENDED BY LEMO

Tools

None

Cables