


Article Number: 596-00497



Description: Solar Label, WARNING ELECTRICAL SHOCK HAZARD, 3.75" x 2.0", VL, Orange/White, 50/roll

Base Data	
Local Order Number	596-00497
Type	WESHLBL
Color	Orange (OG)
Features and benefits	<ul style="list-style-type: none"> • Pre-Printed Vinyl Solar Labels are made with UV-stable inks and materials for durability and weather resistance. • Supplied with an aggressive adhesive to ensure long life. • Meets NEC & IFC standards for printed text, character height, color and outdoor UV stability to pass inspections. • Pre-printed labels offer significant time and cost savings over high priced plastic engraved phenolic placards and lead time purchased markers.
Quantity Per	roll
Product Description	HellermannTyton pre-printed Solar Installation labels are designed to meet the requirements of the 2014 National Electrical Code (NEC 2014) and the 2012 International Fire Code (IFC 2012) as well as being acceptable to the Authority Having Jurisdiction (AHJ). Labels are made with durable UV stable materials and adhesives that are designed to stick to both baked enamel and powder coat surfaces. Where applicable, labels are made using reflective materials for first responder safety. Some pre-printed labels are printable using a thermal transfer printer when variable voltage or series data must be printed and displayed.
Technical Description	Pre-Printed Solar Label, "WARNING - ELECTRICAL SHOCK HAZARD", 3.75" X 2.0", Orange/White
Local Order Number 2	Cross Reference = 10 per pack: 596-00660; Metal Solar Placard 5 pack: 596-00828
Short Description	Solar Label, WARNING ELECTRICAL SHOCK HAZARD, 3.75" x 2.0", VL, Orange/White, 50/roll
Product Dimensions	
Length L (Imperial)	2.0"
Length L (Metric)	50.8mm
Width W (Imperial)	3.75"
Width W (Metric)	95.25mm
Height H (Imperial)	2.0"
Height H (Metric)	50.8mm

596-00497



Material and Specifications		
	Material	Type 443/552, UV Stable Flexible White Vinyl with Acrylic Laminate
	Material Shortcut	443/552
	Adhesive	Acrylic
	Adhesive Operating Temperature	-40°F to +174°F (-40°C to +79°C)
	Halogenfree	Yes
	Minimum Application Temperature	+50°F (+10 °C)
	Operating Temperature	-40°F to +174°F (-40°C to +79°C)
	ROHS Compliant	Yes
	Certification/Specification	UL969
	UL Recognized (US)	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	50
	Package Quantity (Metric)	50
	Customs Number(Schedule B)	3919102055
	Labels per Column	1
	Labels per Row	1