

170-03010



Article Number: 170-03010

Description: Braided Sleeve, Expandable, Flame Retardant, 1.25" Dia, PET, Black, 50 ft/reel

Base Data	Local Order Number	170-03010
	Type	BSPFR1140
	Color	Black (BK)
	Features and Benefits	<ul style="list-style-type: none"> • Treated polyester material contains a combustion inhibitor for use in applications where flame retardancy is required. • Braided design allows sleeving to expand by 150% to accommodate variations in wire bundle and eases installation.
	Quantity Per	reel
	Product Description	A flame retardant woven (threaded) polyester sleeving that is resistant to cuts and abrasion, and contains a combustion inhibitor allowing it to achieve a UL and CSA flame resistance rating of VW-1. Contains white tracer thread for easy identification.
	Short Description	Braided Sleeve, Expandable, Flame Retardant, 1.25" Dia, PET, Black, 50 ft/reel
	Product Dimensions	Length L (Imperial)
Length L (Metric)		15.2m
Reel Length (imperial)		50.0ft
Bundle Diameter Min. (Imperial)		0.75"
Bundle Diameter Min. (Metric)		19.1mm
Bundle Diameter Max. (Imperial)		1.75"
Bundle Diameter Max. (Metric)		44.5mm
Nominal Diameter (Imperial)		1-1/4"
Nominal Diameter (Metric)		31.8mm
Material and Specifications		Material
	Material Shortcut	PET
	Flammability	FAR 25

170-03010



Material and Specifications	Operating Temperature	-94°F to +248°F (-70°C to +125°C)
	ROHS Compliant	Yes
	UL Recognized (US and Canada)	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	50ft
	Package Quantity (Metric)	15.24m
	Customs Number(Schedule B)	3926909987
	Weight (imperial)	0.8lbs
	Weight (Metric)	0.363kg